

Network Working Group  
Internet-Draft  
Updates: [3315](#),3633 (if approved)  
Intended status: Standards Track  
Expires: August 16, 2015

O. Troan  
B. Volz  
Cisco Systems, Inc.  
M. Siodelski  
ISC  
February 12, 2015

**Issues and Recommendations with Multiple Stateful DHCPv6 Options**  
**draft-ietf-dhc-dhcpv6-stateful-issues-11.txt**

Abstract

The Dynamic Host Configuration Protocol for IPv6 (DHCPv6) specification defined two stateful options, IA\_NA and IA\_TA, but did not anticipate the development of additional stateful options. DHCPv6 Prefix Delegation added the IA\_PD option, which is stateful. Applications that use IA\_NA and IA\_PD together have revealed issues that need to be addressed. This document updates [RFC 3315](#) and [RFC 3633](#) to address these issues.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 16, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Conventions . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Handling of Multiple IA Option Types . . . . .	<a href="#">4</a>
<a href="#">4.1.</a>	Placement of Status Codes in an Advertise Message . . . . .	<a href="#">5</a>
<a href="#">4.2.</a>	Advertise Message Processing by a Client . . . . .	<a href="#">7</a>
<a href="#">4.3.</a>	T1/T2 Timers . . . . .	<a href="#">8</a>
<a href="#">4.4.</a>	Renew and Rebind Messages . . . . .	<a href="#">9</a>
<a href="#">4.4.1.</a>	Renew Message . . . . .	<a href="#">9</a>
<a href="#">4.4.2.</a>	Rebind Message . . . . .	<a href="#">10</a>
<a href="#">4.4.3.</a>	Updates to <a href="#">section 18.1.3 of RFC 3315</a> . . . . .	<a href="#">10</a>
<a href="#">4.4.4.</a>	Updates to <a href="#">Section 18.1.4 of RFC 3315</a> . . . . .	<a href="#">12</a>
<a href="#">4.4.5.</a>	Updates to <a href="#">Section 18.1.8 of RFC 3315</a> . . . . .	<a href="#">13</a>
<a href="#">4.4.6.</a>	Updates to <a href="#">Section 18.2.3 of RFC 3315</a> . . . . .	<a href="#">15</a>
<a href="#">4.4.7.</a>	Updates to <a href="#">Section 18.2.4 of RFC 3315</a> . . . . .	<a href="#">16</a>
<a href="#">4.4.8.</a>	Updates to <a href="#">RFC 3633</a> . . . . .	<a href="#">18</a>
<a href="#">4.5.</a>	Confirm Message . . . . .	<a href="#">19</a>
<a href="#">4.6.</a>	Decline Should Not Necessarily Trigger a Release . . . . .	<a href="#">20</a>
<a href="#">4.7.</a>	Multiple Provisioning Domains . . . . .	<a href="#">20</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">21</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">21</a>
<a href="#">7.</a>	Acknowledgements . . . . .	<a href="#">21</a>
<a href="#">8.</a>	References . . . . .	<a href="#">21</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">21</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">21</a>
	Authors' Addresses . . . . .	<a href="#">22</a>



## 1. Introduction

DHCPv6 [[RFC3315](#)] was written without the expectation that additional stateful DHCPv6 options would be developed. DHCPv6 Prefix Delegation [[RFC3633](#)] since added a new stateful option for Prefix Delegation to DHCPv6. Implementation experience of the Customer Edge Router (CER) model described in [[RFC7084](#)] has shown issues with the DHCPv6 protocol in supporting multiple stateful option types, in particular IA\_NA (non-temporary addresses) and IA\_PD (delegated prefixes).

This document describes a number of problems encountered with coexistence of the IA\_NA and IA\_PD option types and specifies changes to the DHCPv6 protocol to address these problems.

The intention of this work is to clarify and, where needed, modify the DHCPv6 protocol specification to support IA\_NA and IA\_PD option types within a single DHCPv6 session.

Note that while IA\_TA (temporary addresses) options may be included with other IA option type requests, these generally are not renewed (there are no T1/T2 times) and have a separate life cycle from IA\_NA and IA\_PD option types. Therefore, the IA\_TA option type is mostly out of scope for this document.

The changes described in this document are intended to be incorporated in a new revision of the DHCPv6 protocol specification ([[I-D.dhwcg-dhc-rfc3315bis](#)]).

## 2. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

## 3. Terminology

In addition to the terminology defined in [[RFC3315](#)], [[RFC3633](#)], and [[RFC7227](#)], the following terminology is used in this document:

Identity association (IA):      Throughout this document, "IA" is used to refer to the Identity Association containing addresses or prefixes assigned to a client and carried in the IA\_NA or IA\_PD options respectively.

IA option types:                This is used to generally mean an IA\_NA and/or IA\_PD option.



Stateful options:	Options that require dynamic binding state per client on the server.
Top-level options:	Top-level options are DHCPv6 options that are not encapsulated within other options, excluding the Relay-Message option. Options encapsulated by Relay-message options, but not by any other option, are still top-level options, whether they appear in a relay agent message or a server message. See [ <a href="#">RFC7227</a> ].

#### **4. Handling of Multiple IA Option Types**

The DHCPv6 specification [[RFC3315](#)] was written with the assumption that the only stateful options were for assigning addresses. DHCPv6 Prefix Delegation [[RFC3633](#)] describes how to extend the DHCPv6 protocol to handle prefix delegation, but does not clearly specify how the DHCP address assignment and prefix delegation co-exist.

If a client requests multiple IA option types, but the server is configured to only offer a subset of them, the client could react in several ways:

1. Reset the state machine and continue to send Solicit messages,
2. Create separate DHCP sessions for each IA option type and continue to Solicit for the unfulfilled IA options, or
3. The client could continue with the single session, and include the unfulfilled IA options in subsequent messages to the server.

Resetting the state machine and continuing to send Solicit messages may result in the client never completing DHCP and is generally not considered a good solution. It can also result in a packet storm if the client does not appropriately rate limit its sending of Solicit messages or there are many clients on the network. Client implementors that follow this approach, are strongly advised to implement the updates to [RFC-3315](#) specified in [[RFC7083](#)].

Creating a separate DHCP session (separate instances of the client state machine) per IA option type, while conceptually simple, causes a number of issues: additional host resources required to create and maintain multiple instances of the state machine in clients, additional DHCP protocol traffic, unnecessary duplication of other configuration options and the potential for conflict, divergence in



that each IA option type specification specifies its 'own' version of the DHCP protocol.

The single session and state machine allows the client to use the best configuration it is able to obtain from a single DHCP server during the configuration exchange. Note, however, that the server may not be configured to deliver the entire configuration requested by the client. In that case the client could continue to operate only using the configuration received, even if other servers can provide the missing configuration. In practice, especially in the case of handling IA\_NA and IA\_PD, this situation should be rare or a temporary operational error. So, it is more likely for the client to get all configuration if it continues, in each subsequent configuration exchange, to request all the configuration information it is programmed to try to obtain, including any stateful configuration options for which no results were returned in previous exchanges.

One major issue of this last approach is that it is difficult to allow it with the current DHCPv6 specifications; in some cases they are not clear enough, and in other cases existing restrictions can make it impossible. This document introduces some clarifications and small modifications to the current specifications to address these concerns.

While all approaches have their own pros and cons, we recommend and focus on approach 3 for this document because it is deemed to work best for common cases of the mixed use of IA\_NA and IA\_PD. But this document does not exclude other approaches. Also, in some corner cases it may not be feasible to maintain a single DHCPv6 session for both IA\_NA and IA\_PD. These corner cases are beyond the scope of this document and may depend on the network in which the client (CER) is designed to operate and on the functions the client is required to perform.

The sections which follow update [RFC 3315](#) and [RFC 3633](#) to accommodate the recommendation, though many of the changes are also applicable even if other approaches are used.

#### **[4.1.](#) Placement of Status Codes in an Advertise Message**

In Reply messages IA specific status codes (i.e., NoAddrsAvail, NotOnLink, NoBinding, NoPrefixAvail) are encapsulated in the IA option. In Advertise messages though, the NoAddrsAvail code is returned at in the top level. This makes sense if the client is only interested in the assignment of the addresses and the failure case is fatal. However, if the client sends both IA\_NA and IA\_PD options in a Solicit message, it is possible that the server offers no addresses





but it offers some prefixes, and the client may choose to send a Request message to obtain the offered prefixes. In this case, it is better if the Status Code option for IA specific status codes is encapsulated in the IA option to indicate that the failure occurred for the specific IA. This also makes the NoAddrsAvail and NoPrefixAvail Status Code option placement for Advertise messages identical to Reply messages.

In addition, how a server formats the Advertise message when addresses are not available has been a point of some confusion and implementations seem to vary (some strictly follow [RFC 3315](#) while others assumed it was encapsulated in the IA option as for Reply messages).

We have chosen the following solution:

Clients MUST be prepared to handle each of the following Advertise messages formats when there are no addresses available (even when no other IA option types were in the Solicit):

1. Advertise containing the IA\_NAs and/or IA\_TAs with encapsulated Status Code option of NoAddrsAvail and no top-level Status Code option.
2. Advertise containing just a top-level Status Code option of NoAddrsAvail and no IA\_NAs/IA\_TAs.
3. Advertise containing a top-level Status Code option of NoAddrsAvail and IA\_NAs and/or IA\_TAs with a Status Code option of NoAddrsAvail.

Note: Clients MUST be prepared to handle the last two formats listed above to facilitate backward compatibility with the servers which have not been updated to this specification.

See [Section 4.2](#) for updated text for [Section 17.1.3 of RFC 3315](#) and [Section 11.1 of RFC 3633](#).

Servers MUST return the Status Code option of NoAddrsAvail encapsulated in an IA\_NA/IA\_TA options and not as a top-level Status Code option of NoAddrsAvail when no addresses will be assigned (1 in the above list). This means that the Advertise response matches the Reply response with respect to the handling of the NoAddrsAvail status.

Replace the following paragraph in [RFC 3315, section 17.2.2](#):



If the server will not assign any addresses to any IAs in a subsequent Request from the client, the server MUST send an Advertise message to the client that includes only a Status Code option with code NoAddrsAvail and a status message for the user, a Server Identifier option with the server's DUID, and a Client Identifier option with the client's DUID.

With:

If the server will not assign any addresses to an IA in a subsequent Request from the client, the server MUST include the IA in the Advertise message with no addresses in the IA and a Status Code option encapsulated in the IA containing status code NoAddrsAvail.

#### **4.2. Advertise Message Processing by a Client**

[RFC3315] specifies that a client must ignore an Advertise message if a server will not assign any addresses to a client, and [RFC3633] specifies that a client must ignore an Advertise message if a server returns the NoPrefixAvail status to a requesting router. Thus, a client requesting both IA\_NA and IA\_PD, with a server that only offers either addresses or delegated prefixes, is not supported by the current protocol specifications.

Solution: a client SHOULD accept Advertise messages, even when not all IA option types are being offered. And, in this case, the client SHOULD include the not offered IA option types in its Request. A client SHOULD only ignore an Advertise message when none of the requested IA options include offered addresses or delegated prefixes. Note that ignored messages MUST still be processed for SOL\_MAX\_RT and INF\_MAX\_RT options as specified in [RFC7083].

Replace [Section 17.1.3 of RFC 3315](#): (existing errata)

The client MUST ignore any Advertise message that includes a Status Code option containing the value NoAddrsAvail, with the exception that the client MAY display the associated status message(s) to the user.

With (this includes the changes made by [RFC7083]):



The client MUST ignore any Advertise message that contains no addresses (IAADDR options encapsulated in IA\_NA or IA\_TA options) and no delegated prefixes (IAPREFIX options encapsulated in IA\_PD options, see [RFC 3633](#)) with the exception that the client:

- MUST process an included SOL\_MAX\_RT option ([RFC 7083](#)),
- MUST process an included INF\_MAX\_RT option ([RFC 7083](#)), and
- MAY display any associated status message(s) to the user.

The client ignoring this Advertise message MUST NOT restart the Solicit retransmission timer.

And, replace:

- The client MAY choose a less-preferred server if that server has a better set of advertised parameters, such as the available addresses advertised in IAs.

With:

- The client MAY choose a less-preferred server if that server has a better set of advertised parameters, such as the available set of IAs, as well as the set of other configuration options advertised.

And, replace the last paragraph of [Section 11.1 of RFC 3633](#) with:

The requesting router MUST ignore any Advertise message that contains no addresses (IAADDR options encapsulated in IA\_NA or IA\_TA options) and no delegated prefixes (IAPREFIX options encapsulated in IA\_PD options, see [RFC 3633](#)) with the exception that the requesting router:

- MUST process an included SOL\_MAX\_RT option ([RFC 7083](#)),
- MUST process an included INF\_MAX\_RT option ([RFC 7083](#)), and
- MAY display any associated status message(s) to the user.

The requesting router ignoring this Advertise message MUST NOT restart the Solicit retransmission timer.

#### [4.3.](#) T1/T2 Timers

The T1 and T2 times determine when the client will contact the server to extend lifetimes of information received in an IA. How should a client handle the case where multiple IA options have different T1 and T2 times?

In a multiple IA option type model, the T1/T2 times are protocol timers, that should be independent of the IA options themselves. If we were to redo the DHCP protocol from scratch the T1/T2 times should be carried in a separate DHCP option.



Solution: The server MUST set the T1/T2 times in all IA options in a Reply or Advertise message to the same value. To deal with the case where servers have not yet been updated to do that, the client MUST select a T1 and T2 time from all IA options which will guarantee that the client will send Renew/Rebind messages not later than at the T1/T2 times associated with any of the client's bindings.

As an example, if the client receives a Reply with T1\_NA of 3600 / T2\_NA of 5760 and T1\_PD of 0 / T2\_PD of 1800, the client SHOULD use the T1\_PD of 0 / T2\_PD of 1800. The reason for this is that a T1 of 0 means that the Renew time is at the client's discretion, but this value cannot be greater than the T2 value (1800).

The following paragraph should be added to Sections [18.2.1](#), [18.2.3](#), and 18.2.4 of [RFC 3315](#):

The T1/T2 times set in each applicable IA option for a Reply MUST be the same values across all IAs. The server MUST determine the T1/T2 times across all of the applicable client's bindings in the Reply. This facilitates the client being able to renew all of the bindings at the same time.

Note: This additional paragraph has also been included in the revised text later for Sections [18.2.3](#) and [18.2.4](#) of [RFC 3315](#).

Changes for client T1/T2 handling are included in [Section 4.4.3](#) and [Section 4.4.4](#).

#### **[4.4. Renew and Rebind Messages](#)**

This section presents issues with handling multiple IA option types in the context of creation and processing the Renew and Rebind messages. It also introduces relevant updates to the [[RFC3315](#)] and [[RFC3633](#)].

##### **[4.4.1. Renew Message](#)**

In multiple IA option type model, the client may include multiple IA options in the Request message, and the server may create bindings only for a subset of the IA options included by the client. For the IA options in the Request message for which the server does not create the bindings, the server sends the IA options in the Reply message with the NoAddrsAvail or NoPrefixAvail status codes.

The client may accept the bindings created by the server, but may desire the other bindings to be created once they become available, e.g. when the server configuration is changed. The client which accepted the bindings created by the server will periodically send a





Renew message to extend their lifetimes. However, the Renew message, as described in the [\[RFC3315\]](#), does not support the ability for the client to extend the lifetimes of the bindings for some IAs, while requesting bindings for other IAs.

Solution: The client, which sends a Renew message to extend the lifetimes of the bindings assigned to the client, should include IA options for these bindings as well as IA options for all other bindings that the client desires but has been unable to obtain. The client and server processing need to be modified. Note that this change makes the server's IA processing of Renew similar to the Request processing.

#### **[4.4.2.](#) Rebind Message**

According to the [Section 4.4.1](#), the client includes IA options in a Renew message for the bindings it desires but has been unable to obtain by sending a Request message, apart from the IA options for the existing bindings.

At time T2, the client stops sending Renew messages to the server and initiates the Rebind/Reply message exchange with any available server. In this case, it should be possible to continue trying to obtain new bindings using the Rebind message if the client failed to get the response from the server to the Renew message.

Solution: The client should continue to include the IA options received from the server and it may include additional IA options to request creation of the additional bindings.

#### **[4.4.3.](#) Updates to [section 18.1.3 of RFC 3315](#)**

Replace [Section 18.1.3 of RFC 3315](#) with the following text:

To extend the valid and preferred lifetimes for the addresses assigned to an IA, the client sends a Renew message to the server from which the addresses were obtained, which includes an IA option for the IA whose address lifetimes are to be extended. The client includes IA Address options within the IA option for the addresses assigned to the IA. The server determines new lifetimes for these addresses according to the administrative configuration of the server. The server may also add new addresses to the IA. The server can remove addresses from the IA by returning IA Address options for such addresses with preferred and valid lifetimes set to zero.

The server controls the time at which the client contacts the server to extend the lifetimes on assigned addresses through the T1



and T2 parameters assigned to an IA. However, as the client Renews/Rebinds all IAs from the server at the same time, the client MUST select a T1 and T2 time from all IA options which will guarantee that the client will send Renew/Rebind messages not later than at the T1/T2 times associated with any of the client's bindings.

At time T1, the client initiates a Renew/Reply message exchange to extend the lifetimes on any addresses in the IA.

If T1 or T2 had been set to 0 by the server (for an IA\_NA) or there are no T1 or T2 times (for an IA\_TA) in a previous Reply, the client may send a Renew or Rebind message, respectively, at the client's discretion.

The client sets the "msg-type" field to RENEW. The client generates a transaction ID and inserts this value in the "transaction-id" field.

The client places the identifier of the destination server in a Server Identifier option.

The client MUST include a Client Identifier option to identify itself to the server. The client adds any appropriate options, including one or more IA options.

For IAs to which addresses have been assigned, the client includes a corresponding IA option containing an IA Address option for each address assigned to the IA. The client MUST NOT include addresses in any IA option that the client did not obtain from the server or that are no longer valid (that have a zero valid lifetime).

The client MAY include an IA option for each binding it desires but has been unable to obtain. This IA option MUST NOT contain any addresses. However, it MAY contain the IA Address option with IPv6 address field set to 0 to indicate the client's preference for the preferred and valid lifetimes for any newly assigned addresses.

The client MUST include an Option Request option (see [section 22.7](#)) to indicate the options the client is interested in receiving. The client MAY include options with data values as hints to the server about parameter values the client would like to have returned.

The client transmits the message according to [section 14](#), using the following parameters:

IRT      REN\_TIMEOUT



MRT	REN_MAX_RT
MRC	0
MRD	Remaining time until T2

The message exchange is terminated when time T2 is reached (see [section 18.1.4](#)), at which time the client begins a Rebind message exchange.

#### **4.4.4. Updates to [Section 18.1.4 of RFC 3315](#)**

Replace [Section 18.1.4 of RFC 3315](#) with the following text:

At time T2 (which will only be reached if the server to which the Renew message was sent at time T1 has not responded), the client initiates a Rebind/Reply message exchange with any available server.

The client constructs the Rebind message as described in 18.1.3 with the following differences:

- The client sets the "msg-type" field to REBIND.
- The client does not include the Server Identifier option in the Rebind message.

The client transmits the message according to [section 14](#), using the following parameters:

IRT	REB_TIMEOUT
MRT	REB_MAX_RT
MRC	0
MRD	Remaining time until valid lifetimes of all addresses in all IAs have expired

If all addresses for an IA have expired the client may choose to include this IA without any addresses (or with only a hint for lifetimes) in subsequent Rebind messages to indicate that the client is interested in assignment of the addresses to this IA.

The message exchange is terminated when the valid lifetimes of all addresses across all IAs have expired, at which time the client uses Solicit message to locate a new DHCP server and sends a Request for the expired IAs to the new server.

#### **4.4.5. Updates to [Section 18.1.8 of RFC 3315](#)**

Replace [Section 18.1.8 of RFC 3315](#) with the following text:

Upon the receipt of a valid Reply message in response to a Solicit (with a Rapid Commit option), Request, Confirm, Renew, Rebind or Information-request message, the client extracts the configuration information contained in the Reply. The client MAY choose to report any status code or message from the status code option in the Reply message.

If the client receives a Reply message with a Status Code containing UnspecFail, the server is indicating that it was unable to process the message due to an unspecified failure condition. If the client retransmits the original message to the same server to retry the desired operation, the client MUST limit the rate at which it retransmits the message and limit the duration of the time during which it retransmits the message.

When the client receives a Reply message with a Status Code option with the value UseMulticast, the client records the receipt of the message and sends subsequent messages to the server through the interface on which the message was received using multicast. The client resends the original message using multicast.

When the client receives a NotOnLink status from the server in response to a Confirm message, the client performs DHCP server solicitation, as described in [section 17](#), and client-initiated configuration as described in [section 18](#). If the client receives any Reply messages that do not indicate a NotOnLink status, the client can use the addresses in the IA and ignore any messages that indicate a NotOnLink status.

When the client receives a NotOnLink status from the server in response to a Request, the client can either re-issue the Request without specifying any addresses or restart the DHCP server discovery process (see [section 17](#)).

The client SHOULD perform duplicate address detection [17] on each of the received addresses in any IAs, on which it has not performed duplicate address detection during processing of any of the previous Reply messages from the server. The client performs the duplicate address detection before using the received addresses for the traffic. If any of the addresses are found to be in use on the link, the client sends a Decline message to the server for those addresses as described in [section 18.1.7](#).





If the Reply was received in response to a Solicit (with a Rapid Commit option), Request, Renew or Rebind message, the client updates the information it has recorded about IAs from the IA options contained in the Reply message:

- Record T1 and T2 times.
- Add any new addresses in the IA option to the IA as recorded by the client.
- Update lifetimes for any addresses in the IA option that the client already has recorded in the IA.
- Discard any addresses from the IA, as recorded by the client, that have a valid lifetime of 0 in the IA Address option.
- Leave unchanged any information about addresses the client has recorded in the IA but that were not included in the IA from the server.

Management of the specific configuration information is detailed in the definition of each option in [section 22](#).

The client examines the status code in each IA individually. If the client receives a NoAddrsAvail status code, the client has received no usable addresses in the IA.

If the client can operate with the addresses obtained from the server the client uses addresses and other information from any IAs that do not contain a Status Code option with the NoAddrsAvail status code. The client MAY include the IAs for which it received the NoAddrsAvail status code, with no addresses, in subsequent Renew and Rebind messages sent to the server, to retry obtaining the addresses for these IAs.

If the client cannot operate without the addresses for the IAs for which it received the NoAddrsAvail status code, the client may try another server (perhaps by restarting the DHCP server discovery process).

If the client finds no usable addresses in any of the IAs, it may either try another server (perhaps restarting the DHCP server discovery process) or use the Information-request message to obtain other configuration information only.

When the client receives a Reply message in response to a Renew or Rebind message, the client:



- sends a Request message if any of the IAs in the Reply message contains the NoBinding status code. The client places IA options in this message for only those IAs for which the server returned the NoBinding status code in the Reply message. The client continues to use other bindings for which the server did not return an error
- sends a Renew/Rebind if any of the IAs is not in the Reply message, but in this case the client **MUST** limit the rate at which it sends these messages, to avoid the Renew/Rebind storm
- otherwise accepts the information in the IA.

When the client receives a valid Reply message in response to a Release message, the client considers the Release event completed, regardless of the Status Code option(s) returned by the server.

When the client receives a valid Reply message in response to a Decline message, the client considers the Decline event completed, regardless of the Status Code option(s) returned by the server.

#### **4.4.6. Updates to [Section 18.2.3 of RFC 3315](#)**

Replace [Section 18.2.3 of RFC 3315](#) with the following text:

When the server receives a Renew message via unicast from a client to which the server has not sent a unicast option, the server discards the Renew message and responds with a Reply message containing a Status Code option with the value UseMulticast, a Server Identifier option containing the server's DUID, the Client Identifier option from the client message, and no other options.

For each IA in the Renew message from a client, the server locates the client's binding and verifies that the information in the IA from the client matches the information stored for that client.

If the server finds the client entry for the IA the server sends back the IA to the client with new lifetimes and, if applicable, T1/T2 times. If the server is unable to extend the lifetimes of an address in the IA, the server **MAY** choose not to include the IA Address option for this address.

The server may choose to change the list of addresses and the lifetimes of addresses in IAs that are returned to the client.

If the server finds that any of the addresses in the IA are not appropriate for the link to which the client is attached, the server returns the address to the client with lifetimes of 0.



For each IA for which the server cannot find a client entry, the server has the following choices depending on the server's policy and configuration information:

- If the server is configured to create new bindings as a result of processing Renew messages, the server SHOULD create a binding and return the IA with allocated addresses with lifetimes and, if applicable, T1/T2 times and other information requested by the client. The server MAY use values in the IA Address option (if included) as a hint.
- If the server is configured to create new bindings as a result of processing Renew messages, but the server will not assign any addresses to an IA, the server returns the IA option containing a Status Code option with the NoAddrsAvail status code and a status message for a user.
- If the server does not support creation of new bindings for the client sending a Renew message, or if this behavior is disabled according to the server's policy or configuration information, the server returns the IA option containing a Status code option with the NoBinding status code and a status message for a user.

The server constructs a Reply message by setting the "msg-type" field to REPLY, and copying the transaction ID from the Renew message into the transaction-id field.

The server MUST include a Server Identifier option containing the server's DUID and the Client Identifier option from the Renew message in the Reply message.

The server includes other options containing configuration information to be returned to the client as described in [section 18.2](#).

The T1/T2 times set in each applicable IA option for a Reply MUST be the same values across all IAs. The server MUST determine the T1/T2 times across all of the applicable client's bindings in the Reply. This facilitates the client being able to renew all of the bindings at the same time.

#### **4.4.7. Updates to [Section 18.2.4 of RFC 3315](#)**

Replace [Section 18.2.4 of RFC 3315](#) with the following text:

When the server receives a Rebind message that contains an IA option from a client, it locates the client's binding and verifies



that the information in the IA from the client matches the information stored for that client.

If the server finds the client entry for the IA and the server determines that the addresses in the IA are appropriate for the link to which the client's interface is attached according to the server's explicit configuration information, the server **SHOULD** send back the IA to the client with new lifetimes and, if applicable, T1/T2 times. If the server is unable to extend the lifetimes of an address in the IA, the server **MAY** choose not to include the IA Address option for this address.

If the server finds the client entry for the IA and any of the addresses are no longer appropriate for the link to which the client's interface is attached according to the server's explicit configuration information, the server returns the address to the client with lifetimes of 0.

If the server cannot find a client entry for the IA, the IA contains addresses and the server determines that the addresses in the IA are not appropriate for the link to which the client's interface is attached according to the server's explicit configuration information, the server **MAY** send a Reply message to the client containing the client's IA, with the lifetimes for the addresses in the IA set to 0. This Reply constitutes an explicit notification to the client that the addresses in the IA are no longer valid. In this situation, if the server does not send a Reply message it silently discards the Rebind message.

Otherwise, for each IA for which the server cannot find a client entry, the server has the following choices depending on the server's policy and configuration information:

- If the server is configured to create new bindings as a result of processing Rebind messages (also see the note about the Rapid Commit option below), the server **SHOULD** create a binding and return the IA with allocated addresses with lifetimes and, if applicable, T1/T2 times and other information requested by the client. The server **MAY** use values in the IA Address option (if included) as a hint.
- If the server is configured to create new bindings as a result of processing Rebind messages, but the server will not assign any addresses to an IA, the server returns the IA option containing a Status Code option with the NoAddrsAvail status code and a status message for a user.





- If the server does not support creation of new bindings for the client sending a Rebind message, or if this behavior is disabled according to the server's policy or configuration information, the server returns the IA option containing a Status Code option with the NoBinding status code and a status message for a user.

When the server creates new bindings for the IA it is possible that other servers also create bindings as a result of receiving the same Rebind message. This is the same issue as in the Discussion under the Rapid Commit option, see [section 22.14](#). Therefore, the server SHOULD only create new bindings during processing of a Rebind message if the server is configured to respond with a Reply message to a Solicit message containing the Rapid Commit option.

The server constructs a Reply message by setting the "msg-type" field to REPLY, and copying the transaction ID from the Rebind message into the transaction-id field.

The server MUST include a Server Identifier option containing the server's DUID and the Client Identifier option from the Rebind message in the Reply message.

The server includes other options containing configuration information to be returned to the client as described in [section 18.2](#).

The T1/T2 times set in each applicable IA option for a Reply MUST be the same values across all IAs. The server MUST determine the T1/T2 times across all of the applicable client's bindings in the Reply. This facilitates the client being able to renew all of the bindings at the same time.

#### **[4.4.8](#). Updates to [RFC 3633](#)**

Replace the following text in [Section 12.1 of RFC 3633](#):

Each prefix has valid and preferred lifetimes whose durations are specified in the IA\_PD Prefix option for that prefix. The requesting router uses Renew and Rebind messages to request the extension of the lifetimes of a delegated prefix.

With:

Each prefix has valid and preferred lifetimes whose durations are specified in the IA\_PD Prefix option for that prefix. The



requesting router uses Renew and Rebind messages to request the extension of the lifetimes of a delegated prefix.

The requesting router MAY include IA\_PD options without any prefixes, i.e. without IA Prefix option or with IPv6 prefix field of IA Prefix option set to 0, in a Renew or Rebind message to obtain bindings it desires but has been unable to obtain. The requesting router MAY set the prefix-length field of the IA Prefix option as a hint to the server. As in [RFC3315], the requesting router MAY also provide lifetime hints in the IA Prefix option.

Replace the following text in [Section 12.2 of RFC 3633](#):

The delegating router behaves as follows when it cannot find a binding for the requesting router's IA\_PD:

With:

For the Renew or Rebind, if the IA\_PD contains no IA Prefix option or it contains an IA Prefix option with the IPv6 prefix field set to 0, the delegating router SHOULD assign prefixes to the IA\_PD according to the delegating router's explicit configuration information. In this case, if the IA\_PD contains an IA Prefix option with the IPv6 prefix field set to 0, the delegating router MAY use the value in the prefix-length field of the IA Prefix option as a hint for the length of the prefixes to be assigned. The delegating router MAY also respect lifetime hints provided by the requesting router in the IA Prefix option.

The delegating router behaves as follows when it cannot find a binding for the requesting router's IA\_PD containing prefixes:

#### **[4.5.](#) Confirm Message**

The Confirm message, as described in [RFC3315], is specific to address assignment. It allows a server without a binding to reply to the message, under the assumption that the server only needs knowledge about the prefix(es) on the link, to inform the client that the address is likely valid or not. This message is sent when e.g. the client has moved and needs to validate its addresses. Not all bindings can be validated by servers and the Confirm message provides for this by specifying that a server that is unable to determine the on-link status MUST NOT send a Reply.

Note: Confirm has a specific meaning and does not overload Renew/Rebind. It also is lower processing cost as the server does NOT need to extend lease times or otherwise send back other configuration options.



The Confirm message is used by the client to verify that it has not moved to a different link. For IAs with addresses, the mechanism used to verify if a client has moved or not, is by matching the link's on-link prefix(es) (typically a /64) against the prefix-length first bits of the addresses provided by the client in the IA\_NA or IA\_TA IA-types. As a consequence Confirm can only be used when the client has an IA with address(es) (IA\_NA or IA\_TA).

A client MUST have a binding including an IA with addresses to use the Confirm message. A client with IAs with addresses as well as other IA-types MAY, depending on the IA-type, use the Confirm message to detect if the client has moved to a different link. A client that does not have a binding with an IA with addresses MUST use the Rebind message instead.

IA\_PD requires verification that the delegating router (server) has the binding for the IAs. In that case a requesting router (client) MUST use the Rebind message in place of the Confirm message and it MUST include all of its bindings, even address IAs.

Note that [Section 18.1.2 of RFC 3315](#) states that a client MUST initiate a Confirm when it may have moved to a new link. This is relaxed to a SHOULD as a client may have determined whether it has or has not moved using other techniques, such as described in [\[RFC6059\]](#). And, as stated above, a client with delegated prefixes, MUST send a Rebind instead of a Confirm.

#### **[4.6.](#) Decline Should Not Necessarily Trigger a Release**

Some client implementations have been found to send a Release message for other bindings they may have received after they determine a conflict and have correctly sent a Decline message for the conflicting address(es).

It is recommended that a client SHOULD NOT send a Release message for other bindings it may have received just because it sent a Decline message. The client SHOULD retain the non-conflicting bindings. The client SHOULD treat the failure to acquire a binding as a result of the conflict, to be equivalent to not having received the binding, insofar as it behaves when sending Renew and Rebind messages.

#### **[4.7.](#) Multiple Provisioning Domains**

This document has assumed that all DHCP servers on a network are in a single provisioning domain and thus should be "equal" in the service that they offer. This was also assumed by [\[RFC3315\]](#) and [\[RFC3633\]](#).



One could envision a network where the DHCP servers are in multiple provisioning domains, and it may be desirable to have the DHCP client obtain different IA types from different provisioning domains. How a client detects the multiple provisioning domains and how it would interact with the multiple servers in these different domains is outside the scope of this document (see [[I-D.ietf-mif-mpvd-arch](#)] and [[I-D.ietf-mif-mpvd-dhcp-support](#)]).

## **5. IANA Considerations**

This specification does not require any IANA actions.

## **6. Security Considerations**

There are no new security considerations pertaining to this document.

## **7. Acknowledgements**

Thanks to many people that contributed to identify the stateful issues addressed by this document and for reviewing drafts of the document, including Ralph Droms, John Brzozowski, Ted Lemon, Hemant Singh, Wes Beebe, Gaurau Halwasia, Bud Millword, Tim Winters, Rob Shakir, Jinmei Tatuya, Andrew Yourtchenko, Fred Templin, Tomek Mrugalski, Suresh Krishnan, and Ian Farrer.

## **8. References**

### **8.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3315] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), July 2003.
- [RFC3633] Troan, O. and R. Droms, "IPv6 Prefix Options for Dynamic Host Configuration Protocol (DHCP) version 6", [RFC 3633](#), December 2003.
- [RFC7083] Droms, R., "Modification to Default Values of SOL\_MAX\_RT and INF\_MAX\_RT", [RFC 7083](#), November 2013.

### **8.2. Informative References**

[I-D.dhcgw-dhc-rfc3315bis]

Mrugalski, T., Siodelski, M., Volz, B., Yourtchenko, A., Richardson, M., Jiang, S., and T. Lemon, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6) bis", [draft-dhcgw-dhc-rfc3315bis-03](#) (work in progress), October 2014.

[I-D.ietf-mif-mpvd-arch]

Anipko, D., "Multiple Provisioning Domain Architecture", [draft-ietf-mif-mpvd-arch-10](#) (work in progress), February 2015.

[I-D.ietf-mif-mpvd-dhcp-support]

Krishnan, S., Korhonen, J., and S. Bhandari, "Support for multiple provisioning domains in DHCPv6", [draft-ietf-mif-mpvd-dhcp-support-00](#) (work in progress), August 2014.

[RFC6059] Krishnan, S. and G. Daley, "Simple Procedures for Detecting Network Attachment in IPv6", [RFC 6059](#), November 2010.

[RFC7084] Singh, H., Beebe, W., Donley, C., and B. Stark, "Basic Requirements for IPv6 Customer Edge Routers", [RFC 7084](#), November 2013.

[RFC7227] Hankins, D., Mrugalski, T., Siodelski, M., Jiang, S., and S. Krishnan, "Guidelines for Creating New DHCPv6 Options", [BCP 187](#), [RFC 7227](#), May 2014.

Authors' Addresses

Ole Troan  
Cisco Systems, Inc.  
Philip Pedersens vei 20  
N-1324 Lysaker  
Norway

Email: [ot@cisco.com](mailto:ot@cisco.com)

Bernie Volz  
Cisco Systems, Inc.  
1414 Massachusetts Ave  
Boxborough, MA 01719  
USA

Email: [volz@cisco.com](mailto:volz@cisco.com)





Marcin Siodelski  
ISC  
950 Charter Street  
Redwood City, CA 94063  
USA

Email: [msiodelski@gmail.com](mailto:msiodelski@gmail.com)