Domain Name System Operations

Internet-Draft

Intended status: Informational
Expires: November 05, 2015

J. Livingood Comcast May 6, 2015

# Responsibility for Authoritative DNSSEC Mistakes draft-livingood-dnsop-auth-dnssec-mistakes-02

# Abstract

DNS Security Extensions (DNSSEC) is now entering widespread deployment. However, domain signing tools and processes are not yet as mature and reliable as is the case for non-DNSSEC-related domain administration tools and processes. Authoritative DNS operators should focus on improving these processes and establishing a high level of quality in their work.

#### Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of  $\underline{\mathsf{BCP}}$  78 and  $\underline{\mathsf{BCP}}$  79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <a href="http://datatracker.ietf.org/drafts/current/">http://datatracker.ietf.org/drafts/current/</a>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 05, 2015.

# Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <a href="BCP-78">BCP 78</a> and the IETF Trust's Legal Provisions Relating to IETF Documents (<a href="http://trustee.ietf.org/license-info">http://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the <a href="Trust Legal Provisions">Trust Legal Provisions</a> and are provided without warranty as described in the Simplified BSD License.

#### Table of Contents

<u>1</u> .	Introduction										2
<u>2</u> .	Domain Validation Failures										2

3. Responsibility for Failures						<u>3</u>
4. Comparison to Other DNS Misconfigurations						3
<u>5</u> . Other Considerations						<u>4</u>
<u>5.1</u> . Security Considerations						4
<u>5.2</u> . Privacy Considerations						<u>4</u>
<u>5.3</u> . IANA Considerations						4
<pre>6. Acknowledgements</pre>						4

Responsibility for DNSSEC Mistakes

May 2015

# 7.2. Informative References 5 Appendix A. Document Change Log 5 Appendix B. Open Issues 5 Author's Address 6

#### 1. Introduction

Internet-Draft

The Domain Name System (DNS), DNS Security Extensions (DNSSEC), and related operational practices are defined extensively [RFC1034] [RFC1035] [RFC4033] [RFC4034] [RFC4035] [RFC4398] [RFC4509] [RFC6781] [RFC5155].

DNSSEC has now entered widespread deployment. However, domain signing tools and processes are not yet as mature and reliable as is the case for non-DNSSEC-related domain administration tools and processes. As a result, operators of DNS recursive resolvers, such as Internet Service Providers (ISPs), occasionally observe domains incorrectly managing DNSSEC-related resource records. This mismanagement triggers DNSSEC validation failures, and then causes large numbers of end users to be unable to reach a domain. Many end users tend interpret this as a failure of their DNS servers, and may switch to a non-validating resolver (reducing their security) or contact their ISP to complain, rather than seeing this as a failure on the part of the domain they wanted to reach.

This document makes clear, however, that responsibility for these failures rests squarely with authoritative domain name operators, as noted in Section 3.

#### 2. Domain Validation Failures

A domain name can fail validation for two general reasons, a legitimate security failure such as due to an attack or compromise of some sort, or as a result of misconfiguration on the part of an domain administrator. As domains transition to DNSSEC the most likely reason for a validation failure will be due to misconfiguration. Thus, domain administrators should be sure to read [RFC6781] in full. They should also pay special attention to Section 4.2, pertaining to key rollovers, which appears to be the cause of many recent validation failures.

In one recent example [DNSSEC-Validation-Failure-Analysis], a specific domain name failed to validate. An investigation revealed that the domain's administrators performed a Key Signing Key (KSK) rollover by (1) generating a new key and (2) signing the domain with the new key. However, they did not use a double-signing procedure for the KSK and a pre-publish procedure for the ZSK. Double-signing refers to signing a zone with two KSKs and then updating the parent zone with the new DS record so that both keys are valid at the same time. This meant that the domain name was signed with the new KSK, but it was not double-signed with the old KSK. So, the new key was used for signing the zone but the old key was not. As a result, the domain could not be trusted and returned an error when trying to reach the domain. Thus, the domain was in a situation where the DNSSEC chain of trust was broken because the Delegation Signer (DS) record pointed to the old KSK, which was no longer used for signing the zone. (A DS record provides a link in the chain of trust for DNSSEC from the parent zone to the child zone - in this case between TLD and domain name.)

# 3. Responsibility for Failures

A domain administrator is solely and completely responsible for managing their domain name(s) and DNS resource records. This includes complete responsibility for the correctness of those resource records, the proper functioning of their authoritative DNS servers, and the correctness of DNS records linking their domain to a top-level domain (TLD) or other higher level domain. The domain owner is also responsible for selection of the authoritative domain administrator, operator, or service provider. Thus, even in cases where some error may be introduced by a third party, whether that is due to an authoritative server software vendor, software tools vendor, domain name registrar, or other organization, these are all parties that the domain administrator has selected and is responsible for managing successfully.

There are some cases where the domain administrator is different than the domain owner. In those cases, a domain owner has delegated operational responsibility to the domain administrator. So no matter whether a domain owner is also the domain administrator or not, the domain administrator is nevertheless operationally responsible for the proper configuration operation of the domain.

So in the case of a domain name failing to successfully validate, when this is due to a misconfiguration of the domain, that is the sole responsibility of the domain administrator.

Any assistance or mitigation responses undertaken by other parties to mitigate the misconfiguration of a domain name by a domain administrator, especially operators of DNS recursive resolvers, are optional and at the pleasure of those parties.

# **4**. Comparison to Other DNS Misconfigurations

Livingood

Expires November 05, 2015

[Page 3]

As noted in <u>Section 3</u> domain administrators are ultimately responsible for managing and ensuring their DNS records are configured correctly. ISPs or other DNS recursive resolver operators cannot and should not correct misconfigured A, CNAME, MX, or other resource records of domains for which they are not authoritative. Expecting non-authoritative entities to protect domain administrators from any misconfiguration of resource records is therefore unrealistic and unreasonable, and in the long-term is harmful to the delegated design of the DNS and could lead to extensive operational instability and/or variation.

#### Other Considerations

# 5.1. Security Considerations

Authoritative domain name operators and domain name owners, in the case of DNSSEC-related mistakes that cause validation failures to occur, should focus on correcting the issue and then improving their processes and tools in the future. During the period of time that their domain cannot be resolved due to a DNSSEC-related mistake, they should not encourage end users to switch to non-validating resolvers, as the use of a non-validating DNS recursive resolver has comparatively less security capabilities than a validating resolver, since one implements DNS Security Extensions and one does not. In addition, if an end user changes to a non-validating resolver they may subject themselves to increased security risks and threats against which DNS Security Extensions may have provided protection.

## **5.2**. Privacy Considerations

There are no privacy considerations in this document.

# **5.3**. IANA Considerations

There are no IANA considerations in this document.

## Acknowledgements

- William Brown

# 7. References

#### 7.1. Normative References

- [RFC1035] Mockapetris, P., "Domain names implementation and specification", STD 13, RFC 1035, November 1987.
- [RFC4033] Arends, R., Austein, R., Larson, M., Massey, D. and S.

Rose, "DNS Security Introduction and Requirements",  $\underline{\text{RFC}}$   $\underline{4033}$ , March 2005.

Livingood

Expires November 05, 2015

[Page 4]

- [RFC4035] Arends, R., Austein, R., Larson, M., Massey, D. and S.
  Rose, "Protocol Modifications for the DNS Security
  Extensions", RFC 4035, March 2005.
- [RFC4398] Josefsson, S., "Storing Certificates in the Domain Name System (DNS)", RFC 4398, March 2006.
- [RFC4509] Hardaker, W., "Use of SHA-256 in DNSSEC Delegation Signer (DS) Resource Records (RRs)", RFC 4509, May 2006.
- [RFC5914] Housley, R., Ashmore, S. and C. Wallace, "Trust Anchor Format", RFC 5914, June 2010.

#### 7.2. Informative References

[DNSSEC-Validation-Failure-Analysis]
 Barnitz, J., Creighton, T., Ganster, C., Griffiths, C. and
 J. Livingood, "Analysis of DNSSEC Validation Failure NASA.GOV", Comcast , January 2012, <a href="http://www.dnssec.comcast.net/">http://www.dnssec.comcast.net/</a>
 DNSSEC Validation Failure NASAGOV 20120118 FINAL.pdf>.

# Appendix A. Document Change Log

[RFC Editor: This section is to be removed before publication]

Individual-00: First version published as an individual draft.

Individual-01: Fixed nits identified by William Brown

Individual-02: Updated prior to IETF-91

WG-00: Renamed at request of DNSOP co-chairs

WG-01: Updated doc to keep it from expiring

WG-02: Removed RFC 2119 reference in XML

# Appendix B. Open Issues

[RFC Editor: This section is to be removed before publication]

Livingood Expires November 05, 2015 [Page 5]

No open issues at this time

Author's Address

Jason Livingood Comcast One Comcast Center 1701 John F. Kennedy Boulevard Philadelphia, PA 19103 US

Email: jason\_livingood@cable.comcast.com

URI: <a href="http://www.comcast.com">http://www.comcast.com</a>