

INTERNET-DRAFT
Intended Status: Informational
Expires: July 27, 2013

L. Fang, Ed.
Cisco
N. Bitar
Verizon
R. Zhang
Alcatel Lucent
M. Daikoku
KDDI
P. Pan
Infinera

January 27, 2013

MPLS-TP Applicability; Use Cases and Design
draft-ietf-mpls-tp-use-cases-and-design-06.txt

Abstract

This document provides applicability, use case studies and network design considerations for the Multiprotocol Label Switching Transport Profile (MPLS-TP). The use cases include Metro Ethernet access and aggregation transport, Mobile backhaul, and packet optical transport.

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/lid-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

Copyright and License Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Terminology	4
3.	MPLS-TP Use Cases	5
3.1.	Metro Access and Aggregation	5
3.2.	Packet Optical Transport	6
3.3.	Mobile Backhaul	7
3.3.1.	2G and 3G Mobile Backhaul	7
3.3.2.	4G/LTE Mobile Backhaul	8
4.	Network Design Considerations	9
4.1.	The role of MPLS-TP	9
4.2.	Provisioning mode	9
4.3.	Standards compliance	9
4.4.	End-to-end MPLS OAM consistency	10
4.5.	PW Design considerations in MPLS-TP networks	10
4.6.	Proactive and on-demand MPLS-TP OAM tools	11
4.7.	MPLS-TP and IP/MPLS Interworking considerations	11
5.	Security Considerations	11
6.	IANA Considerations	12
7.	Acknowledgements	12
8.	References	12
8.1.	Normative References	12
8.2.	Informative References	13
	Authors' Addresses	13
	Contributors' Addresses	14

1. Introduction

This document provides applicability, use case studies and network design considerations for the Multiprotocol Label Switching Transport Profile (MPLS-TP).

In recent years, the urgency for moving from traditional transport technologies, such as SONET/SDH, TDM, and ATM, to new packet technologies has been rising. This is largely due to the fast growing demand for bandwidth, which has been fueled by the following factors:

- 1) The growth of new services. This includes: the tremendous success of data services, such as IPTV and IP Video for content downloading, streaming, and sharing; the rapid growth of mobile services, as a consequence of the explosion of smart phone applications; the continued growth of business VPNs and residential broadband services.
- 2) Network infrastructure evolution. As many legacy transport devices are approaching end of life, Service Providers transition to new packet technologies and evolve their transport network into the next generation packet transport.

As part of MPLS family, MPLS-TP complements existing IP/MPLS technologies; it closes the gaps in the traditional access and aggregation transport to enable end-to-end packet technology solutions in a cost efficient, reliable, and interoperable manner. After several years of industry debate on which packet technology to use, MPLS-TP has emerged as the next generation transport technology of choice for many Service Providers worldwide.

The Unified MPLS strategy - using MPLS from core to aggregation and access (e.g. IP/MPLS in the core, IP/MPLS or MPLS-TP in aggregation and access) appear to be very attractive to many SPs. It streamlines the operation, reduces the overall complexity, and improves end-to-end convergence. It leverages the MPLS experience, and enhances the ability to support revenue generating services.

MPLS-TP is a subset of MPLS functions that meet the packet transport requirements defined in [\[RFC5654\]](#). This subset includes: MPLS data forwarding, pseudo-wire encapsulation for circuit emulation, and dynamic control plane using GMPLS control for LSP and tLDP for pseudo-wire (PW). MPLS-TP also extends previous MPLS OAM functions, such as BFD extension for proactive Connectivity Check and Connectivity Verification (CC-CV) [\[RFC6428\]](#), and Remote Defect Indication (RDI) [\[RFC6428\]](#), LSP Ping Extension for on-demand CC-CV [\[RFC6426\]](#), fault allocation, and remote integrity check. New tools have been defined for alarm suppression with Alarm Indication Signal (AIS) [\[RFC6427\]](#), and switch-over triggering with Link Defect Indication (LDI). Note that since the MPLS OAM feature extensions defined through the process of MPLS-TP development are part of the

MPLS family, the applicability is general to MPLS, and not limited to MPLS-TP.

The requirements of MPLS-TP are provided in MPLS-TP Requirements [RFC 5654], and the architectural framework is defined in MPLS-TP Framework [[RFC5921](#)]. This document's intent is to provide the use case studies and design considerations from a practical point of view based on Service Providers deployments plan as well as actual deployments.

The most common use cases for MPLS-TP include Metro access and aggregation, Mobile Backhaul, and Packet Optical Transport. MPLS-TP data plane architecture, path protection mechanisms, and OAM functionality are used to support these deployment scenarios.

The design considerations discussed in this document include: the role of MPLS-TP in the network; provisioning options; standards compliance; end-to-end forwarding and OAM consistency; compatibility with existing IP/MPLS networks; and optimization vs. simplicity design trade-offs.

2. Terminology

Term	Definition
-----	-----
2G	2nd generation wireless telephone technology
3G	3rd generation of mobile telecommunications technology
4G	4th Generation Mobile network: LTE
ADSL	Asymmetric Digital Subscriber Line
AIS	Alarm Indication Signal
ASNGW	Access Service Network Gateway
ATM	Asynchronous Transfer Mode
BFD	Bidirectional Forwarding Detection
BTS	Base Transceiver Station
CC-CV	Continuity Check and Connectivity Verification
CDMA	Code Division Multiple Access
E-LINE	Ethernet point-to-point connectivity
E-LAN	Ethernet LAN, provides multipoint connectivity
eNB	Evolved Node B
EPC	Evolved Packet Core
E-VLAN	Ethernet Virtual Private LAN
EVDO	Evolution-Data Optimized
G-ACh	Generic Associated Channel
GAL	G-ACh Label
GMPLS	Generalized Multi-Protocol Label Switching
GSM	Global System for Mobile Communications
HSPA	High Speed Packet Access
IPTV	Internet Protocol television

L2VPN	Layer 2 Virtual Private Network
L3VPN	Layer 3 Virtual Private Network
LAN	Local Access Network
LDI	Link Down Indication
LDP	Label Distribution Protocol
LSP	Label Switched Path
LTE	Long Term Evolution
MEP	Maintenance Entity Group End Point
MIP	Maintenance Entity Group Intermediate Point
NMS	Network Management System
MPLS	MultiProtocol Label Switching
MPLS-TP	MultiProtocol Label Switching Transport Profile
MS-PW	Multi-Segment Pseudowire
OAM	Operations, Administration, and Maintenance
OPEX	Operating Expenses
PE	Provider-Edge device
PSW	Packet Data Network Gateway
RAN	Radio Access Network
RDI	Remote Defect Indication
S1	LTE Standardized interface between eNB and EPC
SDH	Synchronous Digital Hierarchy
SGW	Serving Gateway
SLA	Service Level Agreement
SONET	Synchronous Optical Network
S-PE	PW Switching Provider Edge
SP	Service Provider
SRLG	Shared Risk Link Groups
SS-PW	Single-Segment Pseudowire
TDM	Time Division Multiplexing
TFS	Time and Frequency Synchronization
tLDP	Targeted Label Distribution Protocol
VPN	Virtual Private Network
UMTS	Universal Mobile Telecommunications System
X2	LTE Standardized interface between eNBs for handover

3. MPLS-TP Use Cases

3.1. Metro Access and Aggregation

The use of MPLS-TP for Metro access and aggregation transport is the most common deployment scenario observed in the field.

Some operators are building green-field access and aggregation transport infrastructure, while others are upgrading/replacing their existing transport infrastructure with new packet technologies. The existing legacy access and aggregation networks are usually based on TDM or ATM technologies. Some operators are replacing these networks

with MPLS-TP technologies, since legacy ATM/TDM aggregation and access are becoming inadequate to support the rapid business growth and too expensive to maintain. In addition, in many cases the legacy devices are facing End of Sale and End of Life issues. As operators must move forward with the next generation packet technology, the adoption of MPLS-TP in access and aggregation becomes a natural choice. The statistical multiplexing in MPLS-TP helps to achieve higher efficiency compared with the time division scheme in the legacy technologies. MPLS-TP OAM tools and protection mechanisms help to maintain high reliability of transport networks and achieve fast recovery.

As most Service Providers' core networks are MPLS enabled, extending the MPLS technology to the aggregation and access transport networks with a Unified MPLS strategy is very attractive to many Service Providers. Unified MPLS strategy in this document means having end-to-end MPLS technologies through core, aggregation, and access. It reduces OPEX by streamlining operation and leveraging the operational experience already gained with MPLS technologies; it also improves network efficiency and reduces end-to-end convergence time.

The requirements from the SPs for ATM/TDM aggregation replacement often include: i) maintaining the previous operational model, which means providing a similar user experience in NMS, ii) supporting the existing access network, (e.g., Ethernet, ADSL, ATM, TDM, etc.), and connections with the core networks, and iii) supporting the same operational capabilities and services (L3VPN, L2VPN, E-LINE/E-LAN/E-VLAN, Dedicated Line, etc.). MPLS-TP can meet these requirements and in general the requirements defined in [\[RFC5654\]](#) to support a smooth transition.

3.2. Packet Optical Transport

Many SP's transport networks consist of both packet and optical portions. The transport operators are typically sensitive to network deployment cost and operational simplicity. MPLS-TP supports both static provisioning through NMS and dynamic provisioning via the GMPLS control plane. As such, it is viewed as a natural fit in some of the transport networks, where the operators can utilize the MPLS-TP LSP's (including the ones statically provisioned) to manage user traffic as "circuits" in both packet and optical networks, and when they are ready, move to dynamic control plane for greater efficiency.

Among other attributes, bandwidth management, protection/recovery and OAM are critical in Packet/Optical transport networks. In the context of MPLS-TP, each LSP is expected to be associated with a fixed amount of bandwidth in terms of bits-per-second and/or time-slots. OAM is to be performed on each individual LSP. For some of the performance

monitoring (PM) functions, the OAM mechanisms need to be able to transmit and process OAM packets at very high frequency. An overview of MPLS-TP OAM toolset is found in [[RFC6669](#)].

Protection [[RFC6372](#)] is another important element in transport networks. Typically, ring and linear protection can be readily applied in metro networks. However, as long-haul networks are sensitive to bandwidth cost and tend to have mesh-like topology, shared mesh protection is becoming increasingly important.

In some cases, SPs plan to deploy MPLS-TP from their long haul optical packet transport all the way to the aggregation and access in their networks.

[3.3. Mobile Backhaul](#)

Wireless communication is one of the fastest growing areas in communication worldwide. In some regions, the tremendous mobile growth is fueled by the lack of existing land-line and cable infrastructure. In other regions, the introduction of smart phones is quickly driving mobile data traffic to become the primary mobile bandwidth consumer (some SPs have already observed more than 85% of total mobile traffic are data traffic). MPLS-TP is viewed as a suitable technology for Mobile backhaul.

[3.3.1. 2G and 3G Mobile Backhaul](#)

MPLS-TP is commonly viewed as a very good fit for 2G/3G mobile backhaul. 2G (GSM/CDMA) and 3G (UMTS/HSPA/1xEVDO) Mobile Backhaul Networks are still currently dominating the mobile infrastructure.

The connectivity for 2G/3G networks is point to point (P2P). The logical connections are hub-and-spoke. Networks are physically constructed using a star or ring topology. In the Radio Access Network (RAN), each mobile Base Transceiver Station (BTS/Node B) is communicating with a Radio Controller (BSC/RNC). These connections are often statically set up.

Hierarchical or centralized architectures are often used for pre-aggregation and aggregation layers. Each aggregation network interconnects with multiple access networks. For example, a single aggregation ring could aggregate traffic for 10 access rings with a total of 100 base stations.

The technology used today is largely ATM based. Mobile providers are replacing the ATM RAN infrastructure with newer packet technologies. IP RAN networks with IP/MPLS technologies are deployed today by many SPs with great success. MPLS-TP is another suitable choice for Mobile

RAN. The P2P connections from base station to Radio Controller can be set statically to mimic the operation of today's RAN environments; in-band OAM and deterministic path protection can support fast failure detection and switch-over to satisfy the SLA agreements. Bidirectional LSPs may help to simplify the provisioning process. The deterministic nature of MPLS-TP LSP set up can also support packet based synchronization to maintain predictable performance regarding packet delay and jitters. The traffic engineered and co-routed bidirectional properties of an MPLS-TP LSP are of benefit in transporting packet based Time and Frequency Synchronization (TFS) protocols such as [1588overmpls]. However, the choice between an external, physical layer or packet based TFS method is network dependent and thus is out of scope of this document.

3.3.2. 4G/LTE Mobile Backhaul

One key difference between LTE and 2G/3G mobile networks is that the logical connection in LTE is a mesh, while in 2G/3G is a P2P star. In LTE, the base stations eNB/BTS communicate with multiple Network controllers (PSW/SGW or ASNGW), and the radio elements communicate with one another for signal exchange and traffic offload to wireless or wireline infrastructures.

IP/MPLS has a great advantage in any-to-any connectivity environments. Thus, the use of mature IP or L3VPN technologies is particularly common in the design of SP's LTE deployment plans.

The extended OAM functions defined in MPLS-TP, such as in-band OAM and path protection mechanisms bring additional advantages to support SLAs. The dynamic control-plane with GMPLS signaling is especially suited for the mesh environment, to support dynamic topology changes and network optimization.

Some operators are using the same model as in 2G and 3G Mobile Backhaul, which uses IP/MPLS in the core, and MPLS-TP with static provisioning (through NMS) in aggregation and access. The reasoning is as follows: the X2 traffic load in LTE networks currently may be a very small percentage of the total traffic. For example, one large mobile operator observed that X2 traffic was less than one percent of the total S1 traffic. Therefore, optimizing the X2 traffic may not be the design objective in this case. The X2 traffic can be carried through the same static tunnels together with the S1 traffic in the aggregation and access networks, and further forwarded across the IP/MPLS core. In addition, mesh protection may be more efficient with regard to bandwidth utilization, but linear protection and ring protection are often considered simpler by some operators from the point of view of operation maintenance and trouble shooting, and so are widely deployed. In general, using MPLS-TP with static

provisioning for LTE backhaul is a viable option. The design objective of using this approach is to keep the operation simple and use a common model for mobile backhaul, especially during the transition period.

The TFS considerations stated in [Section 3.3.1](#) apply to the 4G/LTE Mobile Backhaul case as well.

4. Network Design Considerations

[4.1.](#) The role of MPLS-TP

The role of MPLS-TP is to provide a solution to help evolve traditional transport towards packet. It is designed to support the transport characteristics/behavior described in [\[RFC5654\]](#). The primary use of MPLS-TP is largely to replace legacy transport technologies, such as SONET/SDH. MPLS-TP is not designed to replace the service support capabilities of IP/MPLS, such as L2VPN, L3VPN, IPTV, Mobile RAN, etc.

[4.2.](#) Provisioning mode

MPLS-TP supports two provisioning modes: i) a mandatory static provisioning mode, which must be supported without dependency on dynamic routing or signaling; and ii) an optional distributed dynamic control plane, which is used to enable dynamic service provisioning.

The decision on which mode to use is largely dependent on the operational feasibility and the stage of network transition. Operators who are accustomed to the transport-centric operational model (e.g., NMS configuration without control plane) typically prefer the static provisioning mode. This is the most common choice in current deployments. The dynamic provisioning mode can be more powerful but it is more suited to operators who are familiar with the operation and maintenance of IP/MPLS technologies or are ready to step up through training and planned transition.

There may be also cases where operators choose to use the combination of both modes. This is appropriate when parts of the network are provisioned in a static fashion and other parts are controlled by dynamic signaling. This combination may also be used to transition from static provisioning to dynamic control plane.

[4.3.](#) Standards compliance

It is generally recognized by SPs that standards compliance is important for lowering cost, accelerating product maturity, achieving

multi-vendor interoperability, and meeting the expectations of their enterprise customers.

MPLS-TP is a joint work between IETF and ITU-T. In April 2008, IETF and ITU-T jointly agreed to terminate T-MPLS and progress MPLS-TP as joint work [[RFC5317](#)]. The transport requirements are provided by ITU-T, the protocols are developed in IETF.

4.4. End-to-end MPLS OAM consistency

End-to-end MPLS OAM consistency is highly desirable in order to enable Service Providers to deploy an end-to-end MPLS solution with a combination of IP/MPLS (for example, in the core including service edge) and MPLS-TP (for example, in the aggregation/access networks). Using MPLS based OAM in MPLS-TP can help achieve such a goal.

4.5. PW Design considerations in MPLS-TP networks

In general, PWs in MPLS-TP work the same as in IP/MPLS networks. Both Single-Segment PW (SS-PW) and Multi-Segment PW (MS-PW) are supported. For dynamic control plane, Targeted LDP (tLDP) is used. In static provisioning mode, PW status is a new PW OAM feature for failure notification. In addition, both directions of a PW must be bound to the same transport bidirectional LSP.

In the common network topology involving multi-tier rings, the design choice is between using SS-PW or MS-PW. This is not a discussion unique to MPLS-TP, as it applies to PW design in general, but it is relevant here, since MPLS-TP is more sensitive to the operational complexities, as noted by operators. If MS-PW is used, Switched PE (S-PE) must be deployed to connect the rings. The advantage of this choice is that it provides domain isolation, which in turn facilitates trouble shooting and allows for faster PW failure recovery. On the other hand, the disadvantage of using S-PE is that it adds more complexity. Using SS-PW is simpler, since it does not require S-PEs, but less efficient because the paths across primary and secondary rings are longer. If operational simplicity is a higher priority, some SPs choose the latter.

Another design trade-off is whether to use PW protection in addition to LSP protection or rely solely on LSP protection. When the MPLS-TP LSPs are protected, if the working LSP fails, the protect LSP assures that the connectivity is maintained and the PW is not impacted. However, in the case of simultaneous failure of both working and protect LSPs, the attached PW would fail. By adding PW protection, and attaching the protect PW to a diverse LSP not in the same Shared Risk Link Group (SRLG), the PW is protected even when the primary PW fails. Clearly, using PW protection adds considerably more

complexity and resource usage, and thus operators often may choose not to use it, and consider protection against single point of failure as sufficient.

4.6. Proactive and on-demand MPLS-TP OAM tools

MPLS-TP provide both proactive and on-demand OAM Tools. As a proactive OAM fault management tool, BFD Connectivity Check (CC) can be sent at regular intervals for Connectivity Check; three missed CC messages (or a configurable number) can trigger the failure protection switch-over. BFD sessions are configured for both working and protecting LSPs.

A design decision is choosing the value of the BFD CC interval. The shorter the interval, the faster the detection time is, but also the higher the resource utilization is. The proper value depends on the application and the service needs.

As an on-demand OAM fault management mechanism, for example when there is a fiber cut, Link Down Indication (LDI) message [[RFC6427](#)] can be generated from the failure point and propagated to the Maintenance Entity Group End Points (MEPs) to trigger immediate switch-over from working to protect path. An Alarm Indication Signal (AIS) can be propagated from the Maintenance Entity Group Intermediate Point (MIP) to the MEPs for alarm suppression.

In general, both proactive and on-demand OAM tools should be enabled to guarantee short switch-over times.

4.7. MPLS-TP and IP/MPLS Interworking considerations

Since IP/MPLS is largely deployed in most SPs' networks, MPLS-TP and IP/MPLS Interworking is inevitable if not a reality. However, Interworking discussion is out of the scope of this document, it is for further study.

5. Security Considerations

Under the use case of Metro access and aggregation, in the scenario where some of the access equipment is placed in facilities not owned by the SP, the static provisioning mode of MPLS-TP is often preferred over the control plane option because it eliminates the possibility of a control plane attack which may potentially impact the whole network. This scenario falls into the Security Reference Model 2 as described in [MPLS-TP Sec FW].

Similar location issues apply to the mobile use cases, since equipment is often placed in remote and outdoor environment, which

can increase the risk of un-authorized access to the equipment.

In general, NMS access can be a common point of attack in all MPLS-TP use cases, and attacks to GAL or G-ACh are unique security treats to MPLS-TP. The MPLS-TP security considerations are discussed in MPLS-TP Security Framework [MPLS-TP Sec FW]. General security considerations for MPLS and GMPLS networks are addressed in Security Framework for MPLS and GMPLS Networks [[RFC5920](#)].

6. IANA Considerations

This document contains no new IANA considerations.

7. Acknowledgements

The authors wish to thank Adrian Farrel for his review as Routing Area Director, Adrian's detailed comments were of great help for improving the quality of this document, and thank Loa Andersson and Adrian Farrel for their continued support and guidance. The authors would also like to thank Weiqiang Cheng for his helpful input on LTE Mobile backhaul based on his knowledge and experience in real world deployment, thank Stewart for his text contribution on timing, thank Andrew Malis for his support and use case discussion, thank Pablo Frank, Lucy Yong, Huub van Helvoort, Tom Petch, and Curtis Villamizar for their comments and suggestions.

8. References

8.1. Normative References

- [RFC5654] Niven-Jenkins, B., Ed., Brungard, D., Ed., Betts, M., Ed., Sprecher, N., and S. Ueno, "Requirements of an MPLS Transport Profile", [RFC 5654](#), September 2009.
- [RFC5920] Fang, L., Ed., "Security Framework for MPLS and GMPLS Networks", [RFC 5920](#), July 2010.
- [RFC5921] Bocci, M., Ed., Bryant, S., Ed., Frost, D., Ed., Levrau, L., and L. Berger, "A Framework for MPLS in Transport Networks", [RFC 5921](#), July 2010.
- [RFC6426] Gray, E., Bahadur, N., Boutros, S., and R. Aggarwal, "MPLS On-Demand Connectivity Verification and Route Tracing", [RFC 6426](#), November 2011.
- [RFC6427] Swallow, G., Ed., Fulignoli, A., Ed., Vigoureux, M., Ed., Boutros, S., and D. Ward, "MPLS Fault Management Operations, Administration, and Maintenance (OAM)",

[RFC 6427](#), November 2011.

- [RFC6428] Allan, D., Ed., Swallow Ed., G., and J. Drake Ed., "Proactive Connectivity Verification, Continuity Check, and Remote Defect Indication for the MPLS Transport Profile", [RFC 6428](#), November 2011.

8.2. Informative References

- [RFC5317] Bryant, S., Ed., and L. Andersson, Ed., "Joint Working Team (JWT) Report on MPLS Architectural Considerations for a Transport Profile", [RFC 5317](#), February 2009.
- [RFC6372] Sprecher, N., Ed., and A. Farrel, Ed., "MPLS Transport Profile (MPLS-TP) Survivability Framework", [RFC 6372](#), September 2011.
- [RFC6669] Sprecher, N. and L. Fang, "An Overview of the Operations, Administration, and Maintenance (OAM) Toolset for MPLS-Based Transport Networks", [RFC 6669](#), July 2012.
- [MPLS-TP Sec FW] Fang, L. Ed., Niven-Jenkins, B., Ed., Mansfield, S., Ed., and R. Graveman, Ed., "MPLS-TP Security Framework," [draft-ietf-mpls-tp-security-framework-07.txt](#), January 2013.
- [1588overmpls], Davari, S., Oren, A., Bhatia, M., Roberts, P., and L. Montini, "Transporting Timing messages over MPLS Networks," [draft-ietf-tictoc-1588overmpls-03.txt](#), October 2012.

Authors' Addresses

Luyuan Fang
Cisco Systems, Inc.
111 Wood Ave. South
Iselin, NJ 08830
United States
Email: lufang@cisco.com

Nabil Bitar
Verizon
40 Sylvan Road
Waltham, MA 02145
United States

Email: nabil.bitar@verizon.com

Raymond Zhang
Alcatel-Lucent
701 Middlefield Road
Mountain View, CA 94043
United States
Email: raymond.zhang@alcatel-lucent.com

Masahiro Daikoku
KDDI corporation
3-11-11.Iidabashi, Chiyodaku, Tokyo
Japan
Email: ms-daikoku@kddi.com

Ping Pan
Infinera
United States
Email: ppan@infinera.com

Contributors' Addresses

Kam Lee Yap
XO Communications
13865 Sunrise Valley Drive,
Herndon, VA 20171
United States
Email: klyap@xo.com

Dan Frost
Cisco Systems, Inc.
United Kingdom
Email: danfrost@cisco.com

Henry Yu
TW Telecom
10475 Park Meadow Dr.
Littleton, CO 80124
United States
Email: henry.yu@twtelecom.com

Jian Ping Zhang
China Telecom, Shanghai
Room 3402, 211 Shi Ji Da Dao
Pu Dong District, Shanghai
China
Email: zhangjp@shtel.com.cn

Lei Wang
Lime Networks
Strandveien 30, 1366 Lysaker
Norway
Email: lei.wang@limenetworks.no

Mach(Guoyi) Chen
Huawei Technologies Co., Ltd.
No. 3 Xinxu Road
Shangdi Information Industry Base
Hai-Dian District, Beijing 100085
China
Email: mach@huawei.com

Nurit Sprecher
Nokia Siemens Networks
3 Hanagar St. Neve Ne'eman B
Hod Hasharon, 45241
Israel
Email: nurit.sprecher@nsn.com