

ROLL Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: March 29, 2021

M. Richardson  
Sandelman Software Works  
R. Jadhav  
Huawei Tech  
September 25, 2020

## **Controlling Secure Network Enrollment in RPL networks draft-ietf-roll-enrollment-priority-03**

### Abstract

[I-D.ietf-6tisch-enrollment-enhanced-beacon] defines a method by which a potential [[I-D.ietf-6tisch-minimal-security](#)] enrollment proxy can announce itself as a available for new Pledges to enroll on a network. The announcement includes a priority for enrollment. This document provides a mechanism by which a RPL DODAG root can disable enrollment announcements, or adjust the base priority for enrollment operation.

### Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 29, 2021.

### Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Protocol Definition . . . . .	<a href="#">4</a>
<a href="#">2.1.</a>	Upwards compatibility . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Security Considerations . . . . .	<a href="#">5</a>
<a href="#">4.</a>	Privacy Considerations . . . . .	<a href="#">6</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">6</a>
<a href="#">6.</a>	Acknowledgements . . . . .	<a href="#">6</a>
<a href="#">7.</a>	References . . . . .	<a href="#">6</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">6</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">7</a>
<a href="#">Appendix A.</a>	Change history . . . . .	<a href="#">8</a>
	Authors' Addresses . . . . .	<a href="#">8</a>

## [1.](#) Introduction

[RFC7554] describes the use of the time-slotted channel hopping (TSCH) mode of [[ieee802154](#)]. [[I-D.ietf-6tisch-minimal-security](#)] and [[I-D.ietf-6tisch-dtsecurity-secure-join](#)] describe mechanisms by which a new node (the "pledge") can use a friendly router as a Join Proxy. [[I-D.ietf-6tisch-enrollment-enhanced-beacon](#)] describes an extension to the 802.15.4 Enhanced Beacon that is used by a Join Proxy to announce its existence such that Pledges can find them.

The term (1)"Join" has been used in documents like [[I-D.ietf-6tisch-minimal-security](#)] to denote the activity of a new node authenticating itself to the network in order to obtain authorization to become a member of the network. This typically involves a cryptographic authentication protocol in which a network credential is provided.

In the context of the [[RFC6550](#)] RPL protocol, the term (2)"Join" has an alternate meaning: that of a node (already authenticating to the network, and already authorized to be a member of the network), deciding which part of the RPL DODAG to attach to. This term "Join" has to do with parent selection processes.

In order to avoid the ambiguity of this term, this document refers to the process (1)"Join" as enrollment, leaving the term "Join" to mean (2)"Join". The term "onboarding" (or IoT Onboarding) is sometimes used to describe the enrollment process. However, the term `_Join`



Proxy\_ is retained with it's meaning from [\[I-D.ietf-6tisch-minimal-security\]](#).

It has become clear that not every routing member of the mesh ought to announce itself as a \_Join Proxy\_. There are a variety of local reasons by which a 6LR might not want to provide the \_Join Proxy\_ function. They include available battery power, already committed network bandwidth, and also total available memory available for Neighbor Cache Entry slots.

There are other situations where the operator of the network would like to selective enable or disable the enrollment process in a particular DODAG.

As the enrollment process involves permitting unencrypted traffic into the best effort part of a (TSCH) network, it would be better to have the enrollment process off when no new nodes are expected.

A network operator might also be able to recognize when certain parts of the network are overloaded and can not accomodate additional enrollment traffic, and it would like to adjust the enrollment priority (the proxy priority field of [\[I-D.ietf-6tisch-enrollment-enhanced-beacon\]](#)) among all nodes in the subtree of a congested link.

This document describes an RPL DIO option that can be used to announce a minimum enrollment priority. Each potential \_Join Proxy\_ would this value as a base on which to add values relating to local conditions. As explained in [\[I-D.ietf-6tisch-enrollment-enhanced-beacon\]](#), higher values decrease the likelihood of an unenrolled node sending enrollment traffic via this path.

A network operator can set this value to the maximum value allowed, effectively disable all new enrollment traffic.

### **1.1. Terminology**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.



## 2. Protocol Definition

The following option is defined to transmission in the DIO issued by the DODAG root. It may also be added by a router on part of the subtree as a result of some (out of scope for this document) management function.

6LRs that see this DIO Option SHOULD increment their minimum enrollment priority if they observe congestion on the channel used for enrollment traffic. The exact mechanism is a local decision, and may be the subject for future work.

A 6LR which would otherwise be willing to act as a `_Join Proxy_`, will examine the minimum priority field, and to that number, add any additional local consideration (such as upstream congestion).

The Enrollment Priority can only be increased by each 6LR in value, to the maximum value of 0x7f.

The resulting priority, if less than 0x7f should enable the `_Join Proxy_` function.

```

      0               1               2
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4
+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   Type = TBD01|Opt Length = 1|R| min. priority   |
+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

`min.priority` a 7 bit field which provides a base value for the Enhanced Beacon Join priority. A value of 0x7f (127) disables the `_Join Proxy_` function entirely.

R a reserved bit that SHOULD be set to 0 by senders, and MUST be ignored by receivers. This reserved bit SHOULD be copied to options created.

This document uses the extensions mechanism designed into [\[RFC6550\]](#). It does not need any mechanism to enable it.

Future work like [\[I-D.ietf-roll-capabilities\]](#) will enable collection of capabilities such as this one in reports to the DODAG root.

### 2.1. Upwards compatibility

A 6LR which did not support this option would not act on it, or copy it into it's DIO messages. Children and grandchildren nodes would therefore not receive any telemetry via that path, and need to assume a default value.



6LRs that support this option, but whose parent does not send it SHOULD assume a value of 0x40 as their base value. The nodes then adjust this base value based upon their observed congestion, emitting their adjusted DIO value to their children.

A 6LR downstream of a 6LR where there was an interruption in the telemetry could err in two directions: \* if the value implied by the base value of 0x40 was too low, then a 6LR might continue to attract enrollment traffic when none should have been collected. This is a stressor for the network, but this would also be what would occur without this option at all. \* if the value implied by the base value of 0x40 was too high, then a 6LR might deflect enrollment traffic to other parts of the DODAG tree, possibly refusing any enrollment traffic at all. In order for this to happen, some significant congestion must be seen in the sub-tree where the implied 0x40 was introduced. The 0x40 is only the half-way point, so if such an amount of congestion was present, then this sub-tree of the DODAG simply winds up being more cautious than it needed to be.

It is possible that the temporal alternation of the above two situations might introduce cycles of accepting and then rejecting enrollment traffic. This is something an operator should consider if when they incrementally deploy this option to an existing LLN. In addition, an operator would be unable to turn off enrollment traffic by sending a maximum value enrollment priority to the sub-tree. This situation is unfortunate, but without this option, the the situation would occur all over the DODAG, rather than just in the sub-tree where the option was omitted.

### 3. Security Considerations

As per [RFC7416], RPL control frames either run over a secured layer 2, or use the [RFC6550] Secure DIO methods. This option can be placed into either a "clear" (layer-2 secured) DIO, or a layer-3 Secure DIO. As such this option will have both integrity and confidentiality mechanisms applied to it.

A malicious node (that was part of the RPL control plane) could see these options and could, based upon the observed minimal enrollment priority signal a confederate that it was a good time to send malicious join traffic.

Such as a malicious node, being already part of the RPL control plane, could also send DIOs with a different minimal enrollment priority which would cause downstream mesh routers to change their `_Join Proxy_` behaviour.





Lower minimal priorities would cause downstream nodes to accept more pledges than the network was expecting, and higher minimal priorities cause the enrollment process to stall.

The use of layer-2 or layer-3 security for RPL control messages prevents the above two attacks, by preventing malicious nodes from becoming part of the control plane. A node that is attacked and has malware placed on it creates vulnerabilities in the same way such an attack on any node involved in Internet routing protocol does. The rekeying provisions of [[I-D.ietf-6tisch-minimal-security](#)] exist to permit an operator to remove such nodes from the network easily.

#### **4. Privacy Considerations**

There are no new privacy issues caused by this extension.

#### **5. IANA Considerations**

Allocate a new number TBD01 from Registry RPL Control Message Options. This entry should be called Minimum Enrollment Priority.

#### **6. Acknowledgements**

This has been reviewed by Pascal Thubert and Thomas Wattenye.

#### **7. References**

##### **7.1. Normative References**

- [I-D.ietf-6tisch-enrollment-enhanced-beacon]  
Dujovne, D. and M. Richardson, "IEEE 802.15.4 Information Element encapsulation of 6TiSCH Join and Enrollment Information", [draft-ietf-6tisch-enrollment-enhanced-beacon-14](#) (work in progress), February 2020.
- [I-D.ietf-6tisch-minimal-security]  
Vucinic, M., Simon, J., Pister, K., and M. Richardson, "Constrained Join Protocol (CoJP) for 6TiSCH", [draft-ietf-6tisch-minimal-security-15](#) (work in progress), December 2019.
- [ieee802154]  
IEEE standard for Information Technology, ., "IEEE Std. 802.15.4, Part. 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks", n.d., <http://standards.ieee.org/findstds/standard/802.15.4-2015.html>.



- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC6550] Winter, T., Ed., Thubert, P., Ed., Brandt, A., Hui, J., Kelsey, R., Levis, P., Pister, K., Struik, R., Vasseur, JP., and R. Alexander, "RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks", [RFC 6550](#), DOI 10.17487/RFC6550, March 2012, <<https://www.rfc-editor.org/info/rfc6550>>.
- [RFC7416] Tsao, T., Alexander, R., Dohler, M., Daza, V., Lozano, A., and M. Richardson, Ed., "A Security Threat Analysis for the Routing Protocol for Low-Power and Lossy Networks (RPLs)", [RFC 7416](#), DOI 10.17487/RFC7416, January 2015, <<https://www.rfc-editor.org/info/rfc7416>>.
- [RFC7554] Watteyne, T., Ed., Palattella, M., and L. Grieco, "Using IEEE 802.15.4e Time-Slotted Channel Hopping (TSCH) in the Internet of Things (IoT): Problem Statement", [RFC 7554](#), DOI 10.17487/RFC7554, May 2015, <<https://www.rfc-editor.org/info/rfc7554>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

## **7.2. Informative References**

- [I-D.ietf-6tisch-architecture]  
Thubert, P., "An Architecture for IPv6 over the TSCH mode of IEEE 802.15.4", [draft-ietf-6tisch-architecture-29](#) (work in progress), August 2020.
- [I-D.ietf-6tisch-dtsecurity-secure-join]  
Richardson, M., "6tisch Secure Join protocol", [draft-ietf-6tisch-dtsecurity-secure-join-01](#) (work in progress), February 2017.
- [I-D.ietf-6tisch-terminology]  
Palattella, M., Thubert, P., Watteyne, T., and Q. Wang, "Terms Used in IPv6 over the TSCH mode of IEEE 802.15.4e", [draft-ietf-6tisch-terminology-10](#) (work in progress), March 2018.



[I-D.ietf-roll-capabilities]

Jadhav, R., Thubert, P., Richardson, M., and R. Sahoo,  
"RPL Capabilities", [draft-ietf-roll-capabilities-07](#) (work  
in progress), September 2020.

[RFC8137] Kivinen, T. and P. Kinney, "IEEE 802.15.4 Information  
Element for the IETF", [RFC 8137](#), DOI 10.17487/RFC8137, May  
2017, <<https://www.rfc-editor.org/info/rfc8137>>.

[RFC8366] Watsen, K., Richardson, M., Pritikin, M., and T. Eckert,  
"A Voucher Artifact for Bootstrapping Protocols",  
[RFC 8366](#), DOI 10.17487/RFC8366, May 2018,  
<<https://www.rfc-editor.org/info/rfc8366>>.

## **Appendix A. Change history**

version 00.

### Authors' Addresses

Michael Richardson  
Sandelman Software Works

Email: [mcr+ietf@sandelman.ca](mailto:mcr+ietf@sandelman.ca)

Rahul Arvind Jadhav  
Huawei Tech

Email: [rahul.ietf@gmail.com](mailto:rahul.ietf@gmail.com)