Teas Working Group Internet Draft

Intended status: Informational

Expires: August 2017

Young Lee Huawei

Sergio Belotti Nokia

> Dhruv Dhody Huawei

Daniele Ceccarelli Ericsson

> Bin Young Yun ETRI

February 7, 2017

# Information Model for Abstraction and Control of TE Networks (ACTN)

draft-ietf-teas-actn-info-model-00.txt

Abstract

This draft provides an information model for Abstraction and Control of Traffic Engineered (TE) networks (ACTN).

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at http://www.ietf.org/ietf/lid-abstracts.txt

Lee-Belotti

Expires August 7, 2017

[Page 1]

The list of Internet-Draft Shadow Directories can be accessed at <a href="http://www.ietf.org/shadow.html">http://www.ietf.org/shadow.html</a>.

This Internet-Draft will expire on August 7, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the <u>Trust Legal Provisions</u> and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<u>1</u> .	Introduction <u>3</u>
	<u>1.1</u> . Terminology
<u>2</u> .	ACTN Common Interfaces Information Model
	2.1. VN Action Primitives7
	2.1.1. VN Instantiate
	2.1.2. VN Modify
	2.1.3. VN Delete
	2.1.4. VN Update
	2.1.5. VN Path Compute
	2.1.6. VN Query
	2.1.7. TE Update (for TE resources)
	2.2. VN Objects
	2.2.1. VN Identifier
	2.2.2. VN Service Characteristics
	2.2.3. VN End-Point
	2.2.4. VN Objective Function
	2.2.5. VN Action Status
	2.2.6. VN Associated LSP
	2.2.7. VN Computed Path
	2.2.8. VN Service Preference
	2.3. Mapping of VN Primitives with VN Objects
3.	References

Lee-Belotti

Expire August 7, 2017

[Page 2]

<u>3.1</u> . Normative References <u>17</u>
3.2. Informative References <u>17</u>
<u>4</u> . Contributors <u>18</u>
Contributors' Addresses <u>18</u>
Authors' Addresses <u>18</u>
Appendix A: ACTN Applications <u>19</u>
A.1. Coordination of Multi-destination Service
Requirement/Policy <u>19</u>
A.2. Application Service Policy-aware Network Operation21
A.3. Network Function Virtualization Service Enabled
Connectivity
A.4. Dynamic Service Control Policy Enforcement for
Performance and Fault Management
A.5. E2E VN Survivability and Multi-Layer (Packet-Optical)
Coordination for Protection/Restoration

# **1**. Introduction

This draft provides an information model for the requirements identified in the ACTN requirements [ACTN-Req] and the ACTN interfaces identified in the ACTN architecture and framework document [ACTN-Frame].

The purpose of this draft is to put all information elements of ACTN in one place before proceeding to development work necessary for protocol extensions and data models.

The ACTN reference architecture identified a three-tier control hierarchy as depicted in Figure 1:

- Customer Network Controllers (CNC)
- Multi-Domain Service Coordinator (MDSC)
- Physical Network Controllers (PNC).



Figure 1: A Three-tier ACTN control hierarchy

The two interfaces with respect to the MDSC, one north of the MDSC and the other south of the MDSC are referred to as CMI (CNC-MDSC Interface) and MPI (MDSC-PNC Interface), respectively. It is intended to model these two interfaces and derivative interfaces thereof (e.g., MDSC to MSDC in a hierarchy of MDSCs) with one common model.

<u>Appendix A</u> provides some relevant ACTN use-cases extracted from [<u>ACTN-Req</u>]. <u>Appendix A</u> is information only and may help readers understand the context of key use-cases addressed in [<u>ACTN-Req</u>].

# **<u>1.1</u>**. Terminology

- o A Virtual Network is a client view (typically a network slice) of the transport network. It is presented by the provider as a set of physical and/or abstracted resources. Depending on the agreement between client and provider various VN operations and VN views are possible. There are three aspects related to VN:
  - VN Creation: VN could be pre-configured and created via static negotiation between customer and provider. In other cases, VN could also be created dynamically based

Lee-Belotti

Expire August 7, 2017

[Page 4]

on the request from the customer with given SLA attributes which satisfy the customer's objectives.

- 2) Dynamic Operations: VN could be further modified and deleted based on customer request to request changes in the network resources reserved for the customer. The customer can further act upon the virtual network resources to perform E2E tunnel management (setup/release/modify). These changes will incur subsequent LSP management on the operator's level.
- 3) VN View: (a) VN can be seen as an (or set of) e2e tunnel(s) from a customer point of view where an e2e tunnel is referred as a VN member. Each VN member (i.e., e2e tunnel) can then be formed by recursive aggregation of lower level paths at a provider level. Such end to end tunnels may comprise of customer end points, access links, intra domain paths and inter-domain link. In this view VN is thus a list of VN members. (b) VN can also be seen as a terms of topology comprising of physical and abstracted nodes and links. The nodes in this case include physical customer end points, border nodes, and internal nodes as well as abstracted nodes. Similarly the links includes physical access, inter-domain and intradomain links as well as abstracted links. The abstracted nodes and links in this view can be pre-negotiated or created dynamically.
- o A Virtual Network Service (VNS) is the creation and offering of a Virtual Network by a provider to a customer in accordance with SLA agreements reached between them (e.g., re satisfying the customer's objectives).
- o Abstraction is the process of applying policy to the available TE information within a domain, to produce selective information that represents the potential ability to connect across the domain. Thus, abstraction does not necessarily offer all possible connectivity options, but it presents a general view of potential connectivity according to the policies that determine how the domain's administrator wants to allow the domain resources to be used [RFC7926].
- o Abstract topology: Every lower controller in the provider network, when is representing its network topology to a higher layer, it may want to selective hide details of the actual network topology, as suggested for abstraction in [RFC7926]. In such case, an abstract topology may be used for this purpose.

Lee-Belotti Expire August 7, 2017 [Page 5]

Abstract topology enhances scalability for the MDSC to operate multi-domain networks.

## 2. ACTN Common Interfaces Information Model

This section provides ACTN common interface information model to describe in terms of primitives, objects, their properties (represented as attributes), their relationships, and the resources for the service applications needed in the ACTN context.

Basic primitives (messages) are required between the CNC-MDSC and MDSC-PNC controllers. These primitives can then be used to support different ACTN network control functions like network topology request/query, VN service request, path computation and connection control, VN service policy negotiation, enforcement, routing options, etc.

The standard interface is described between a client controller and a server controller. A client-server relationship is recursive between a CNC and a MDSC and between a MDSC and a PNC. In the CMI, the client is a CNC while the server is a MDSC. In the MPI, the client is a MDSC and the server is a PNC. There may also be MDSC-MDSC interface(s) that need to be supported. This may arise in a hierarchy of MDSCs in which workloads may need to be partitioned to multiple MDSCs.

Basic primitives (messages) are required between the CNC-MDSC and MDSC-PNC controllers. These primitives can then be used to support different ACTN network control functions like network topology request/query, VN service request, path computation and connection control, VN service policy negotiation, enforcement, routing options, etc.

At a minimum, the following VN action primitives should be supported:

- VN Instantiate (See <u>Section 2.1.1</u>. for the description)
- VN Modify (See <u>Section 2.1.2</u>. for the description)
- VN Delete (See <u>Section 2.1.3</u>. for the description)
- VN Update ((See <u>Section 2.1.4</u>. for the description)
- VN Path Compute (See <u>Section 2.1.5</u>. for the description)

Lee-Belotti

Expire August 7, 2017

[Page 6]

- VN Query (See <u>Section 2.1.6</u>. for the description)

In addition to VN action primitives, TE Update primitive should also be supported (See <u>Section 2.1.7</u>. for the description).

# **2.1**. VN Action Primitives

This section provides a list of main primitives necessary to satisfy ACTN requirements specified in [ACTN-REQ].

<VN Action> describes main primitives. VN Action can be one of the following primitives: (i) VN Instantiate; (ii) VN Modify; (iii) VN Delete; (iv) VN Update; (v) VN Path Compute; (vi) VN Query.

# 2.1.1. VN Instantiate

<VN Instantiate> refers to an action from customers/applications to request their VNs. This primitive can also be applied from an MDSC to a PNC requesting a VN (if the domain the PNC supports can instantiate the entire VN) or a part of VN elements. Please see the definition of VN in the <u>section 2</u>.

#### 2.1.2. VN Modify

<VN Modify> refers to an action from customers/applications to modify an existing VN (i.e., instantiated VN). This primitive can also be applied from an MDSC to a PNC requesting a VN (if the domain the PNC supports can instantiate the entire VN) or a part of VN elements.

Lee-Belotti

Expire August 7, 2017

[Page 7]

### 2.1.3. VN Delete

<VN Delete> refers to an action from customers/applications to delete an existing VN. This primitive can also be applied from an MDSC to a PNC requesting a VN (if the domain the PNC supports can instantiate the entire VN) or a part of VN elements.

## 2.1.4. VN Update

<VN Update> refers to any update to the VN that need to be updated to the subscribers. VN Update fulfills a push model at CMI level, to make aware customers of any specific changes in the topology details related to VN instantiated.

Note the VN Update means the connection-related information (e.g., LSPs) update that has association with VNs.

## 2.1.5. VN Path Compute

<VN Path Compute> consists of Request and Reply. Request refers to an action from customers/applications to request a VN path computation. This primitive can also be applied from an MDSC to a PNC requesting a VN (if the domain the PNC supports can instantiate the entire VN) or a part of VN elements.

<VN Path Compute> Reply refers to the reply in response to <VN Path Compute> Request.

<VN Path Compute> Request/Reply is to be differentiated from a VN
Instantiate. The purpose of VN Path Compute is a priori exploration
to estimate network resources availability and getting a list of
possible paths matching customer/applications constraints. To make
this type of request Customer/application controller can have a
shared (with lower controller) view of an abstract network topology
on which to get the constraints used as input in a Path Computation
request. The list of paths obtained by the request can be used by
customer/applications to give path constrains during VNS
connectivity request and to compel the lower level controller (e.g.
MDSC) to select the path that Client/application controller has
chosen among the set of paths returned by the Path Computation
primitives. The importance of this primitives is for example in a
scenario like multi-domain in which the optimal path obtained by an
orchestrator as sum of optimal paths for different domain controller

Lee-Belotti

Expire August 7, 2017

[Page 8]

cannot be the optimal path in the Client/application controller prospective. This only applies between CNC and MDSC.

#### 2.1.6. VN Query

<VN Query> refers to any query pertaining to the VN that has been already instantiated. VN Query fulfills a pull model and permit to get topology view.

<VN Query Reply> refers to the reply in response to <VN Query>.

#### 2.1.7. TE Update (for TE resources)

<TE Update> it is a primitives specifically related to MPI interface to provide TE resource update between any domain controller towards MDSC regarding the entire content of any "domain controller" TE topology or an abstracted filtered view of TE topology depending on negotiated policy.

<TE Update> ::= [<Abstraction>]<TE-topology...>

<TE-topology> ::= <TE-Topology-reference> <Node-list> <Link-list>

<Node-list> ::= <Node>[<Node-list>]

<Node> ::= <Node> <TE-Termination Points>

<Link-list> ::= <Link>[<Link-list>]

Where

<Abstraction> provides information on level of abstraction (as determined a priori).

<TE-topology-reference> ::= information related to the specific tetopology related to nodes and links present in this TE-topology.

<Node-list> ::= detailed information related to a specific node belonging to a te-topology e.g. te-node-attributes [TE-TOPO].

<Link-list> ::= information related to the specific link related belonging to a te-topology e.g. te-link-attributes [TE-TOPO].

Lee-Belotti Expire August 7, 2017

<TE-Termination Points> ::= information details associated to the termination point of te-link related to a specific node e.g. interface-switching-capability [TE-TOPO].

## 2.2. VN Objects

This section provides a list of objects associated to VN action primitives.

# 2.2.1. VN Identifier

<VN Identifier> is a unique identifier of the VN.

## 2.2.2. VN Service Characteristics

VN Service Characteristics describes the customer/application requirements against the VNs to be instantiated.

<VN Service Characteristics> ::= <VN Connectivity Type>

(<VN Traffic Matrix>...)

<VN Survivability>

Where

<VN Connectivity Type> ::= <P2P>|<P2MP>|<MP2MP>|<MP2P>|<Multidestination>

The Connectivity Type identifies the type of required VN Service. In addition to the classical type of services (e.g. P2P/P2MP etc.), ACTN defines the "multi-destination" service that is a new P2P service where the end points are not fixed. They can be chosen among a list of pre-configured end points or dynamically provided by the CNC.

<VN Traffic Matrix> ::= <Bandwidth>

[<VN Constraints>]

The VN Traffic Matrix represents the traffic matrix parameters required against the service connectivity required and so the VN request instantiation between service related Access Points [ACTN-Frame]. Bandwidth is a mandatory parameter and a number of optional constrains can be specified in the <VN Constrains> (e.g. diversity,

Lee-Belotti

Expire August 7, 2017

[Page 10]

cost). They can include objective functions and TE metrics bounds as specified in [<u>RFC5441</u>].

Further details on the VN constraints are specified below:

<VN Constraints> ::= [<Layer Protocol>]

[<Diversity>]

[<Shared Risk>]

<Metric>

Where:

<Layer Protocol> Identifies the layer at which the VN service is requested. It could be for example MPLS, ODU, and OCh.

<Diversity> This allows asking for diversity constraints for a VN Instantiate/Modify or a VN Path Compute. For example, a new VN or a path is requested in total diversity from an existing one (e.g. diversity exclusion).

<Diversity> ::= <VN-exclusion> (<VN-id>...) |

<VN-E2E Tunnel-exclusion> (<Tunnel-id>...)

<Shared Risk> Based on the realization of VN required, group of physical resources can be impacted by the same risk. An E2E tunnel can be impacted by this shared risk. This is used to get the SRLG associated with the different tunnels composing a VN.

<Metric> can include all the Metrics (cost, delay, delay variation, latency), bandwidth utilization parameters defined and referenced by [<u>RFC3630</u>] and [<u>RFC7471</u>].

<VN Survivability> describes all attributes related to the VN recovery level and its survivability policy enforced by the customers/applications.

<VN Survivability> ::= <VN Recovery Level>

[<VN Tunnel Recovery Level>]

[<VN Survivability Policy>]

Where:

Lee-Belotti

Expire August 7, 2017

[Page 11]

<VN Recovery Level> It is a value representing the requested level of resiliency required against the VN. The following values are defined:

 Unprotected VN
 VN with per tunnel recovery: The recovery level is defined against the tunnels composing the VN and it is specified in the <VN Tunnel Recovery Level>.

<VN Tunnel Recovery Level> ::= <0:1>|<1+1>|<1:1>|<1:N>|<M:N>|

<On the fly restoration>

The VN Tunnel Recovery Level indicates the type of protection or restoration mechanism applied to the VN. It augments the recovery types defined in [RFC4427].

<VN Survivability Policy> ::= [<Local Reroute Allowed>]

[<Domain Preference>]

[<Push Allowed>]

[<Incremental Update>]

Where:

<Local Reroute Allowed> is a delegation policy to the Server to allow or not a local reroute fix upon a failure of the primary LSP.

<Domain Preference> is only applied on the MPI where the MDSC
(client) provides a domain preference to each PNC
(server).e.g. when a inter-domain link fails, then PNC can
choose the alternative peering with this info.

<Push Allowed> is a policy that allows a server to trigger an updated VN topology upon failure without an explicit request from the client. Push action can be set as default unless otherwise specified.

<Incremental Update> is another policy that triggers an incremental update from the server since the last period of

Lee-Belotti

Expire August 7, 2017

[Page 12]

update. Incremental update can be set as default unless otherwise specified.

#### 2.2.3. VN End-Point

<VN End-Point> Object describes the VN's customer end-point characteristics.

<VN End-Point> ::= (<Access Point Identifier>

[<Access Link Capability>]

[<Source Indicator>])...

Where:

<Access point identifier> It represents a unique identifier of the client end-point. They are used by the customer to ask for the setup of a virtual network creation. A <VN End-Point> is defined against each AP in the network and is shared between customer and provider. Both the customer and the provider will map it against his own physical resources.

<Access Link Capability> An optional object that identifies the capabilities of the access link related to the given access point. (e.g., max-bandwidth, bandwidth availability, etc.)

<Source Indicator> indicates if an End-point is source or not.

## 2.2.4. VN Objective Function

The VN Objective Function applies to each VN member (i.e., each E2E tunnel) of a VN.

The VN Objective Function can reuse objective functions defined in [RFC5541] section 4.

For a single path computation, the following objective functions are defined:

o MCP is the Minimum Cost Path with respect to a specific metric (e.g. shortest path).

Lee-Belotti

Expire August 7, 2017

Internet-Draft

o MLP is the Minimum Load Path, that means find a path composted by te-link least loaded.o MBP is the Maximum residual Bandwidth Path.

For a concurrent path computation, the following objective functions are defined:

o MBC is to Minimize aggregate Bandwidth Consumption.o MLL is to Minimize the Load of the most loaded Link.o MCC is to Minimize the Cumulative Cost of a set of paths.

## 2.2.5. VN Action Status

<VN Action Status> is the status indicator whether the VN has been successfully instantiated, modified, or deleted in the server network or not in response to a particular VN action.

Note that this action status object can be implicitly indicated and thus not included in any of the VN primitives discussed in  $\frac{\text{Section}}{2.3}$ .

### 2.2.6. VN Associated LSP

<VN Associated LSP> describes the instantiated LSPs that is associated with the VN. <VN Associated LSP> is used between each domain PNC and the MDSC as part of VN Update once the VN is instantiated in each domain network and when CNC want to have more details about the topology instantiated as consequence of a VN Instantiate.

<VN Associated LSP> ::= <VN Identifier> (<LSP>...)

### 2.2.7. VN Computed Path

The VN Computed Path is the list of paths obtained after the VN path computation request from higher controller. Note that the computed path is to be distinguished from the LSP. When the computed path is signaled in the network (and thus the resource is reserved for that path), it becomes an LSP.

<VN Computed Path> ::= (<Path>...)

Lee-Belotti

Expire August 7, 2017

# 2.2.8. VN Service Preference

This section provides VN Service preference. VN Service is defined in <u>Section 2</u>.

<VN Service Preference> ::= [<Location Service Preference >]

[<Client-specific Preference >]

[<End-Point Dynamic Selection Preference >]

Where

<Location Service Preference describes the End-Point Location's
(e.g. Data Centers) support for certain Virtual Network Functions
(VNFs) (e.g., security function, firewall capability, etc.)and is
used to find the path that satisfies the VNF constraint.</pre>

<Client-specific Preference> describes any preference related to Virtual Network Service (VNS) that application/client can enforce via CNC towards lower level controllers. For example, permission the correct selection from the network of the destination related to the indicated VNF It is e.g. the case of VM migration among data center and CNC can enforce specific policy that can permit MDSC/PNC to calculate the correct path for the connectivity supporting the data center interconnection required by application.

<End-Point Dynamic Selection Preference> describes if the End-Point (e.g. Data Center) can support load balancing, disaster recovery or VM migration and so can be part of the selection by MDSC following service Preference enforcement by CNC.

#### **<u>2.3</u>**. Mapping of VN Primitives with VN Objects

This section describes the mapping of VN Primitives with VN Objects based on <u>Section 2.2</u>.

<VN Instantiate> ::= <VN Service Characteristics>

<VN Objective Function>

<VN End-Point>

Lee-Belotti

## Expire August 7, 2017

[Page 15]

ACTN Info Model

[<VN Service Preference>]

<VN Modify> ::= <VN identifier>

<VN Service Characteristics>

[<VN Objective Function>]

<VN End-Point>

[<VN Service Preference>]

<VN Delete> ::= <VN Identifier>

<VN Update> :: = <VN Identifier> <VN Associated LSP>

<VN Path Compute Request> ::= <VN Service Characteristic>

<VN Objective Function>

<VN End-Point>

<VN Path Compute Reply> ::= <VN Computed Path>

<VN Query> ::= <VN Identifier>

<VN Query Reply> ::= <VN Identifier>

<VN Associated LSP>

Lee-Belotti Expire August 7, 2017 [Page 16]

# **<u>3</u>**. References

# 3.1. Normative References

[DRAFT-SER-AWARE] Dhruv Dhody, Qin Wu, Vishwas Manral, Zafar Ali, and Kenji Kumaki, "Extensions to the Path Computation Element Communication Protocol (PCEP) to compute service aware Label Switched Path (LSP).," June 2016, draft-ietfpce-pcep-service-aware-10.

# 3.2. Informative References

- [ACTN-Req] Y. Lee, et al., "Requirements for Abstraction and Control of Transport Networks", <u>draft-lee-teas-actn-requirements</u>, work in progress.
- [ACTN-Frame] D. Ceccarelli, et al., "Framework for Abstraction and Control of Transport Networks", <u>draft-ceccarelli-teas-</u> <u>actn-framework</u>, work in progress.
- [Stateful-PCE] E. Crabbe, et al., "PCEP Extensions for Stateful PCE", <u>draft-ietf-pce-stateful-pce</u>, work in progress.
- [RFC5541] JL. Le Roux, JP. Vasseur and Y. Lee, "Encoding of Objective Functions in the Path Computation Element Communication Protocol (PCEP)", <u>RFC 5541</u>, June 2009.
- [RFC7926] A.Farrel, et al., "Problem Statement and Architecture for Information Exchange between Interconnected Traffic-Engineered Networks", <u>RFC 7926</u>, July 2016.

Lee-Belotti

Expire August 7, 2017

# 4. Contributors

Contributors' Addresses

Authors' Addresses

Young Lee (Editor) Huawei Technologies 5340 Legacy Drive Plano, TX 75023, USA Phone: (469)277-5838 Email: leeyoung@huawei.com

Sergio Belotti (Editor) Alcatel Lucent Via Trento, 30 Vimercate, Italy Email: sergio.belotti@alcatel-lucent.com

Dhruv Dhody Huawei Technologies, Divyashree Technopark, Whitefield Bangalore, India Email: dhruv.ietf@gmail.com

Daniele Ceccarelli Ericsson Torshamnsgatan,48 Stockholm, Sweden Email: daniele.ceccarelli@ericsson.com

Bin Young Yun ETRI Email: byyun@etri.re.kr

Haomian Zheng Huawei Technologies Email: zhenghaomian@huawei.com

Xian Zhang Huawei Technologies Email: zhang.xian@huawei.com

Lee-Belotti

Expire August 7, 2017

[Page 18]

Internet-Draft

Appendix A: ACTN Applications





Lee-Belotti Expire August 7, 2017 [Page 19]

Figure A.1 shows how VN service policies from the CNC are incorporated by the MDSC to support multi-destination applications. Multi-destination applications refer to applications in which the selection of the destination of a network path for a given source needs to be decided dynamically to support such applications.

Data Center selection problems arise for VM mobility, disaster recovery and load balancing cases. VN's service policy plays an important role for virtual network operation. Service policy can be static or dynamic. Dynamic service policy for data center selection may be placed as a result of utilization of data center resources supporting VNs. The MDSC would then incorporate this information to meet the service objective of this application.

## A.2. Application Service Policy-aware Network Operation



Figure A.2: Application Service Policy-aware Network Operation

Lee-Belotti Expire August 7, 2017 [Page 21]

This scenario is similar to the previous case in that the VN service policy for the application can be met by a set of multiple destinations that provide the required virtual network functions (VNF). Virtual network functions can be, for example, security functions required by the VN application. The VN service policy by the CNC would indicate the locations of a certain VNF that can be fulfilled. This policy information is critical in finding the optimal network path subject to this constraint. As VNFs can be dynamically moved across different DCs, this policy should be dynamically enforced from the CNC to the MDSC and the PNCs.

# A.3. Network Function Virtualization Service Enabled Connectivity



Figure A.3: Network Function Virtualization Service Enabled Connectivity

Lee-Belotti Expire August 7, 2017 [Page 23]

Network Function Virtualization Services are usually setup between customers' premises and service provider premises and are provided mostly by cloud providers or content delivery providers. The context may include, but not limited to a security function like firewall, a traffic optimizer, the provisioning of storage or computation capacity where the customer does not care whether the service is implemented in a given data center or another. The customer has to provide (and CNC is providing this) the type of VNF he needs and the policy associated with it (e.q. metric like estimated delay to reach where VNF is located in the DC). The policy linked to VNF is requested as part of the VN instantiation. These services may be hosted virtually by the provider or physically part of the network. This allows the service provider to hide his own resources (both network and data centers) and divert customer requests where most suitable. This is also known as "end points mobility" case and introduces new concepts of traffic and service provisioning and resiliency (e.g., Virtual Machine mobility).

A.4. Dynamic Service Control Policy Enforcement for Performance and Fault Management

> +----+ Customer Network Controller 1 +----+ 1.Traffic|/|\4.Traffic|/|\Monitor&||Monitor|8.Traffic Optimize | | Result 5.Service | | modify & Policy | | modify& | optimize \|/ | optimize Req.\|/ | result +----+ Multi-domain Service Coordinator +----+ 2. Path | /|\3.Traffic | /|\ Monitor | | Monitor | |7.Path Request | Result 6.Path | modify & | modify& | optimize \|/ | optimize Req.\|/ | result +----+ | Physical Network Controller |

Figure A.4: Dynamic Service Control for Performance and Fault Management

Figure A.4 shows the flow of dynamic service control policy enforcement for performance and fault management initiated by customer per VN. The feedback loop and filtering mechanism tailored for VNs performed by the MDSC differentiates this ACTN scope from traditional network management paradigm. VN level dynamic OAM data model is a building block to support this capability.

Lee-Belotti

# A.5. E2E VN Survivability and Multi-Layer (Packet-Optical) Coordination for Protection/Restoration



Figure A.5: E2E VN Survivability and Multi-layer Coordination for Protection and Restoration

Figure A.5 shows the need for E2E protection/restoration control coordination that involves CNC, MDSC and PNCs to meet the VN survivability requirement. VN survivability requirement and its policy need to be translated into multi-domain and multi-layer network protection and restoration scenarios across different controller types. After an E2E path is setup successfully, the MDSC has a unique role to enforce policy-based flexible VN survivability requirement by coordinating all PNC domains.

As seen in Figure A.5, multi-layer (i.e., packet/optical) coordination is a subset of this E2E protection/restoration control operation. The MDSC has a role to play in determining an optimal protection/restoration level based on the customer's VN survivability requirement. For instance, the MDSC needs to interface the PNC for packet core as well as the PNC for optical core and enforce protection/restoration policy as part of the E2E protection/restoration. Neither the PNC for packet core nor the PNC for optical core is in a position to be aware of the E2E path and its protection/restoration situation. This role of the MDSC is unique for this reason. In some cases, the MDSC will have to determine and enforce optical bypass to find a feasible reroute path upon packet core network failure which cannot be resolved the packet core network itself.

To coordinate this operation, the PNCs will need to update its domain level abstract topology upon resource changes due to a network failure or other factors. The MDSC will incorporate all these update to determine if an alternative E2E reroute path is necessary or not based on the changes reported from the PNCs. It will need to update the E2E abstract topology and the affected CN's VN topology in real-time. This refers to dynamic synchronization of topology from Physical topology to abstract topology to VN topology.

MDSC will also need to perform the path restoration signaling to the affected PNCs whenever necessary.

Lee-Belotti