

Internet Engineering Task Force  
Internet Draft  
Category: Informational

Adam Roach  
Ericsson Inc.  
March 2000  
Expires September 2000  
<[draft-roach-sip-acb-00.txt](mailto:draft-roach-sip-acb-00.txt)>

## Automatic Call Back Service in SIP

### Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or cite them other than as "work in progress".

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This document is an individual submission to the IETF. Comments should be directed to the authors.

### Abstract

This document describes a proposed implementation of an Automatic Call Back (ACB) service using SIP. This service is sometimes referred to as "camp on extension," "call again," "automatic redial," and "automatic recall."

## **1. Introduction**

Most services that exist in the public switched telephony network (PSTN) can be implemented trivially using SIP [[1](#)] , either by itself or with currently proposed extensions.

An efficient implementation of the ACB service, however, cannot be accomplished without a mechanism for notification when a called party has become free. This document proposes a method of implementing this functionality using the SUBSCRIBE and NOTIFY methods defined in "Call Event Notification in SIP" [[2](#)] .

## **2. Service Description**



Typically, the caller initiates a call in the normal fashion for their access device (e.g. dialing a number, selecting an entry from an address book application). When the user receives indication of "ringing" or "busy," they may choose to activate the ACB service. The method of activation will vary depending on the access device. For a hardware phone, there will typically be a dedicated "callback" button; PC-based clients may have a menu option and/or a hot key; and PSTN bridges may play a series of prompts to guide the user in activating the service. The user receives confirmation of service activation.

Once the callee's device becomes available, the caller's phone will indicate that the ACB service has been triggered. For hardware phones and PSTN bridges, this will typically be a distinctive ring; for PC-based clients, it may be an audio alert accompanied by a dialogue box.

The user responds to this alerting as if he were answering an incoming call. Upon doing so, he receives indication of the far end alerting, and the call proceeds as normal.

At any time before the ACB service is triggered by the callee's device becoming available, the caller may cancel outstanding ACM requests.

### **3. "Event" header value**

This service uses an event type of "terminal-free" in its SUBSCRIBE and NOTIFY messages. This event is defined to occur whenever a logical terminal transitions to an idle state (i.e. has no ongoing calls).

### **4. Example Messages**

The following sections give example messages for various ACB-related scenarios. Some details, such as SDP bodies and "Via:" headers, have been omitted for the sake of clarity.

#### **4.1. Requesting notification with SUBSCRIBE (callee busy)**

```
INVITE sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 INVITE
Contact: sip:jpublic@terminal17.isp.net
Content-Type: application/sdp
```



SIP/2.0 486 Busy  
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=638bec5a6758941  
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a  
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net  
CSeq: 5231 INVITE  
Content-Length: 0

ACK sip:exuadam@ws592.ericsson.com SIP/2.0  
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=638bec5a67589416288  
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a  
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net  
CSeq: 5231 ACK  
Content-Length: 0

Notice that, since this is a non-call-related subscription, the Call-ID is unique and does not match the previous INVITE request.

SUBSCRIBE sip:exuadam@ws592.ericsson.com SIP/2.0  
To: Adam Roach <sip:adam.roach@ericsson.com>  
From: Joe Public <sip:joe.public@ietf.org>;tag=8a553c7c-38bebcbl  
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net  
CSeq: 16939 SUBSCRIBE  
Contact: sip:jpublic@terminal17.isp.net  
Expires: 14400  
Event: terminal-free  
Content-Length: 0

SIP/2.0 200 OK  
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=346538bebcbl50e  
From: Joe Public <sip:joe.public@ietf.org>;tag=8a553c7c-38bebcbl  
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net  
CSeq: 16939 SUBSCRIBE  
Expires: 3600  
Content-Length: 0

#### **4.2. Requesting notification with SUBSCRIBE (no answer)**

This call flow demonstrates the flow of messages if a user decides to activate the ACB service after the callee's terminal has started alerting, but before the callee answers.



```
INVITE sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 INVITE
Contact: sip:jpublic@terminal17.isp.net
Content-Type: application/sdp
```

```
SIP/2.0 180 Ringing
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=638bec5a6758941
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 INVITE
Content-Length: 0
```

Notice that, since this is a non-call-related subscription, the Call-ID is unique and does not match the previous INVITE request.

```
SUBSCRIBE sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=8a553c7c-38bebc
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net
CSeq: 16939 SUBSCRIBE
Contact: sip:jpublic@terminal17.isp.net
Expires: 14400
Event: terminal-free
Content-Length: 0
```

```
SIP/2.0 200 OK
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=346538bebcbl50e
From: Joe Public <sip:joe.public@ietf.org>;tag=8a553c7c-38bebc
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net
CSeq: 16939 SUBSCRIBE
Expires: 3600
Content-Length: 0
```

Now that the service is activated, the client can cancel the INVITE transaction.

```
CANCEL sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 CANCEL
Content-Length: 0
```





```
SIP/2.0 200 OK
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 CANCEL
Content-Length: 0
```

```
SIP/2.0 487 Call Canceled
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=638bec5a6758941
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 INVITE
Content-Length: 0
```

```
ACK sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=638bec5a6758941
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-0000000a
Call-Id: 34a6-38bec5a6-61103dd1-3@terminal17.isp.net
CSeq: 5231 ACK
Content-Length: 0
```

#### **4.3. Conveying terminal-free status using NOTIFY**

The NOTIFY request contains the same Call-ID as the SUBSCRIBE that asked for it.

```
NOTIFY sip:jpublic@terminal17.isp.net SIP/2.0
To: Joe Public <sip:joe.public@ietf.org>
From: Adam Roach <sip:adam.roach@ericsson.com>;tag=38bebelc-4953
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net
CSeq: 15739 NOTIFY
Contact: sip:exuadam@ws592.ericsson.com
Event: terminal-free
Content-Length: 0
```

```
SIP/2.0 200 OK
To: Joe Public <sip:joe.public@ietf.org>;tag=346e38bebe434931fb51f33
From: Adam Roach <sip:adam.roach@ericsson.com>;tag=38bebelc-4953
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net
CSeq: 15739 NOTIFY
Content-Length: 0
```

Now, a brand new INVITE is issued to begin a call to the newly-freed terminal.



```
INVITE sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-7265482
Call-Id: 355e-38bed457-269136c2-6@terminal17.isp.net
CSeq: 17960 INVITE
Contact: sip:jpublic@terminal17.isp.net
Content-Type: application/sdp
```

```
SIP/2.0 180 Ringing
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=55e38bed45700ca
From: Joe Public <sip:joe.public@ietf.org>;tag=38bec5a6-7265482
Call-Id: 355e-38bed457-269136c2-63@terminal17.isp.net
CSeq: 17960 INVITE
Content-Length: 0
```

The call now continues as normal

#### **4.4. Cancelling a previous ACB request**

```
SUBSCRIBE sip:exuadam@ws592.ericsson.com SIP/2.0
To: Adam Roach <sip:adam.roach@ericsson.com>
From: Joe Public <sip:joe.public@ietf.org>;tag=8f21337c-38a8191
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net
CSeq: 7837 SUBSCRIBE
Contact: sip:jpublic@terminal17.isp.net
Expires: 0
Event: terminal-free
Content-Length: 0
```

```
SIP/2.0 200 OK
To: Adam Roach <sip:adam.roach@ericsson.com>;tag=213985987f9872a
From: Joe Public <sip:joe.public@ietf.org>;tag=8f21337c-38a8191
Call-Id: 3465-38bebcbl-5e86e396-6@terminal17.isp.net
CSeq: 7837 SUBSCRIBE
Expires: 0
Content-Length: 0
```

## **5. References**

- [1] M. Handley/H. Schulzrinne/E. Schooler/J. Rosenberg, "SIP: Session Initiation Protocol", [RFC 2543](#), IETF; March 1999.
- [2] Adam Roach, "Event Notification in SIP", Internet Draft [<draft-roach-sip-subscribe-notify-00.txt>](#), IETF; March 2000. Work in progress.



## **6. Security Considerations**

This draft introduces no security considerations beyond those discussed in the referenced documents.

## **7. Author's Address**

Adam Roach  
Ericsson Inc.  
Mailstop L-04  
851 International Pkwy.  
Richardson, TX 75081  
USA  
Phone: 972-583-7594  
Fax: 972-669-0154  
E-Mail: adam.roach@ericsson.com

