

Link State Routing Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: September 10, 2020

Y. Wang, Ed.  
T. Zhou, Ed.  
Huawei  
R. Pang, Ed.  
China Unicom  
March 09, 2020

## **Extensions to OSPF for Advertising IFIT Node Capability draft-wang-lsr-ospf-ifit-node-capability-02**

### Abstract

This document defines a way for an Open Shortest Path First (OSPF) router originating the RI LSA to announce IFIT node capabilities within the entire routing domain. A new optional TLV is extended to the OSPF RI Opaque LSA [[RFC7770](#)] to carry the IFIT node capability information. Such advertisements enable IFIT applications in an operational network domain. Here, the term "OSPF" includes both OSPFv2 and OSPFv3.

### Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

### Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 10, 2020.

## Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">2</a>
<a href="#">1.1.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Concepts</a>	<a href="#">3</a>
<a href="#">2.1.</a>	<a href="#">IFIT Domain</a>	<a href="#">3</a>
<a href="#">2.2.</a>	<a href="#">IFIT Node Capability Information</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">IFIT Node Capabilities Advertisement</a>	<a href="#">3</a>
<a href="#">4.</a>	<a href="#">IANA Considerations</a>	<a href="#">5</a>
<a href="#">4.1.</a>	<a href="#">TLVs within the body of the OSPF RI Opaque LSA</a>	<a href="#">5</a>
<a href="#">5.</a>	<a href="#">Security Considerations</a>	<a href="#">5</a>
<a href="#">6.</a>	<a href="#">Acknowledgements</a>	<a href="#">5</a>
<a href="#">7.</a>	<a href="#">References</a>	<a href="#">5</a>
<a href="#">7.1.</a>	<a href="#">Normative References</a>	<a href="#">5</a>
<a href="#">7.2.</a>	<a href="#">Informative References</a>	<a href="#">6</a>
	<a href="#">Authors' Addresses</a>	<a href="#">6</a>

## [1.](#) Introduction

IFIT provides a complete framework architecture and a reflection-loop working solution for on-path flow telemetry [[I-D.song-opsawg-ifit-framework](#)]. At present, there are a family of emerging on-path flow telemetry techniques, including In-situ OAM (IOAM) [[I-D.ietf-ippm-ioam-data](#)], PBT [[I-D.song-ippm-postcard-based-telemetry](#)], IOAM Direct Export (DEX) [[I-D.ioamteam-ippm-ioam-direct-export](#)], Enhanced Alternate Marking (EAM) [[I-D.zhou-ippm-enhanced-alternate-marking](#)], etc. IFIT is a solution focusing on network domains. The "network domain" consists of a set of network devices or entities within a single administration. For example, a network domain can be one or more IGP routing domains. The family of emerging on-path flow telemetry techniques may be selectively or partially implemented in different vendors' devices as an emerging feature for various use cases of



application-aware network operations. Hence, in order to enable IFIT applications in a network domain, IFIT node capabilities SHOULD be advertised by every OSPF router in the IGP routing domains.

### **1.1. Terminology**

OSPF: Open Shortest Path First

RI: Router Information

LSA: Link State Advertisement

## **2. Concepts**

### **2.1. IFIT Domain**

IFIT is expected to be deployed in a specific domain referred as the IFIT domain. An IFIT domain may cross multiple network domains. One network domain may consist of multiple IFIT domains. Within the IFIT domain, the IFIT data fields of flow information head MAY be updated by network nodes that the packet traverses.

### **2.2. IFIT Node Capability Information**

Each IFIT node is configured with a node-id which uniquely identifies a node within the associated IFIT domain. To accommodate the different use cases or requirements of in-situ flow information telemetry, IFIT data fields updated by network nodes fall into different categories which are referred as different IFIT option types, including IOAM Trace Option-Types [[I-D.ietf-ippm-ioam-data](#)], IOAM Edge-to-Edge (E2E) Option-Type [[I-D.ietf-ippm-ioam-data](#)], IOAM DEX Option-Type [[I-D.ioamteam-ippm-ioam-direct-export](#)] and Enhanced Alternate Marking (EAM) Option-Type [[I-D.zhou-ippm-enhanced-alternate-marking](#)]. So IFIT Option Types SHOULD be carried in IFIT node capability advertisement.

## **3. IFIT Node Capabilities Advertisement**

Given that OSPF uses the options field in LSAs and hello packets to advertise optional router capabilities [[RFC7770](#)], this document defines a new IFIT Node Capability TLV within the body of the OSPF RI Opaque LSA [[RFC7770](#)] to carry the IFIT node capabilities of the router originating the RI LSA. The IFIT Node Capability TLV is composed of three fields, a two-octet Type field, a two-octet Length field, and a 4-octet Value field. The Type field indicates the type of items in the Value field. The Length field indicates the length of the Value field in octets. The Value field indicates the IFIT Node



Capability, which is a 4-octet IFIT Option Type-enabled Flag. The TLV is padded to 4-octet alignment.

The IFIT Node-capability Sub-TLV has the following format:





Fig. 1 IFIT Node Capability sub-TLV Format

Type: To be assigned by IANA

Length: A 8-bit field that indicates the length of the value portion in octets and will be a multiple of 4 octets dependent on the number of capabilities advertised.

IFIT Option Type-enabled Flag: A 4-octet field, which is defined as following:



Where:

p-Flag: IOAM Pre-allocated Trace Option Type-enabled flag. If p bit is set (1), the router is capable of IOAM Pre-allocated Trace [[I-D.ietf-ippm-ioam-data](#)].

i-Flag: IOAM Incremental Trace Option Type-enabled flag. If i bit is set (1), the router is capable of IOAM Incremental Tracing [[I-D.ietf-ippm-ioam-data](#)].

d-Flag: IOAM DEX Option Type-enabled flag. If d bit is set (1), the router is capable of IOAM DEX [[I-D.ioamteam-ippm-ioam-direct-export](#)].

e-Flag: IOAM E2E Option Type-enabled flag. If e bit is set (1), the router is capable of IOAM E2E processing [[I-D.ietf-ippm-ioam-data](#)].



m-Flag: Enhanced Alternative Marking enabled flag. If m bit is set (1), then the router is capable of processing Enhanced Alternative Marking packets [[I-D.zhou-ippm-enhanced-alternate-marking](#)].

Reserved: MUST be set to zero upon transmission and ignored upon receipt.

An IFIT node SHALL be capable of more than one IFIT option types. So in this case, IFIT Option Type-enabled Flag bitmap SHOULD has more than one bit being set.

#### **4. IANA Considerations**

Note to RFC Editor: this section may be removed on publication as an RFC.

##### **4.1. TLVs within the body of the OSPF RI Opaque LSA**

This document makes the following registrations for a TLV type of the new IFIT Node Capability TLV proposed in [Section 3](#) of this document within the body of the OSPF RI Opaque LSA.

+-----+	-----+
Type	Description
+-----+	-----+
TBD	IFIT Node Capability
+-----+	-----+

#### **5. Security Considerations**

This document introduces new TLVs within the existing OSPF RI Opaque LSA. It does not introduce any new security risks to OSPF.

#### **6. Acknowledgements**

#### **7. References**

##### **7.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC7770] "Extensions to OSPF for Advertising Optional Router Capabilities", <<https://www.rfc-editor.org/info/rfc7770>>.

## 7.2. Informative References

- [I-D.ietf-ippm-ioam-data]  
"Data Fields for In-situ OAM".
- [I-D.ioamteam-ippm-ioam-direct-export]  
"In-situ OAM Direct Exporting",  
<<https://datatracker.ietf.org/doc/draft-ioamteam-ippm-ioam-direct-export/>>.
- [I-D.song-ippm-postcard-based-telemetry]  
"Postcard-based On-Path Flow Data Telemetry",  
<<https://datatracker.ietf.org/doc/draft-song-ippm-postcard-based-telemetry/>>.
- [I-D.song-opsawg-ifit-framework]  
"In-situ Flow Information Telemetry Framework",  
<<https://datatracker.ietf.org/doc/draft-song-opsawg-ifit-framework/>>.
- [I-D.zhou-ippm-enhanced-alternate-marking]  
"Enhanced Alternate Marking Method",  
<<https://datatracker.ietf.org/doc/draft-zhou-ippm-enhanced-alternate-marking/>>.

### Authors' Addresses

Yali Wang (editor)  
Huawei  
156 Beiqing Rd., Haidian District  
Beijing  
China

Email: wangyalil1@huawei.com

Tianran Zhou (editor)  
Huawei  
156 Beiqing Rd., Haidian District  
Beijing  
China

Email: zhoutianran@huawei.com

Ran Pang (editor)  
China Unicom  
9 Shouti South Rd., Haidian District  
Beijing  
China

Email: pangran@chinaunicom.com